



















Add-on devices

		Description	Width (mm)	Cat. No.	Ref. No.	Pack.
 <p>Auxiliary contact block 1/2 mod.</p> 	<p>To be coupled to Series E90, E90P EFI, EHFI, D/HD90 1CO</p>		9	H	676034	10
		<p>To be coupled to Series E880 1CO</p>	9	H	671597	10
	 <p>Tripping-signal or auxiliary contact block 1/2 mod.</p>	<p>To be coupled to Series E880 1CO</p>	9	S/H	671599	10
		 <p>Tripping-signal switch with reset button 1/2 mod.</p>	<p>To be coupled to Series E90, E90P EFI, EHFI, D/HD90 1CO</p>	9	S/H	676035
<p>2CO</p>	9		SRH/HH	567819	10	
<p>To be coupled to Series E880 1CO</p>	9			671602	10	
 <p>Miniature circuit breakers interlock 1/2 mod.</p> 	Panelboard switch	9	NLVS	676038	10	
 <p>Remote release 1 mod.</p> 	<p>To be coupled to Series E90, EC90, EC91, E90P EFI, EHFI, D/HD90 AC 24 - 60V, DC 24 - 48V</p>	18	NF4	567820	10	
	<p>AC 110 - 415V, DC 110 - 125V</p>	18	NF5	567821	10	
 <p>Undervoltage trip 1 mod.</p> 	<p>To be coupled to Series E90, EC90, EC91, E90P EFI, EHFI, D/HD90 can be subsequently fitted to both sides of miniature circuit breakers</p>	18	NUVR 230	676039	1	
	<p>AC 230V</p>	18	NUVR 12	676040	1	
	<p>AC/DC 12V</p>	18	NUVR 24	676041	1	
	<p>AC/DC 24V</p>	18	NUVR 48	676042	1	
	<p>AC/DC 48V</p>	18				
	<p>To be coupled to Series E880 AC 24 - 60V, DC 24 - 48V</p>	18				
<p>AC 110 - 415V, DC 110 - 125V</p>	18		546532	1		
 <p>Remote drive 3 mod.</p> 	<p>To be coupled to Series E90, EC90, EC91, E90P EFI, EHFI, D/HD90</p>	54	NFA	676043	1	

Accessories

	Description	Cat. No.	Ref. No.	Pack.
 	For Series E90 Padlocking bracket for E90 + S90	KS	624929	2
	Sealing plate for 4 poles	EPP	669486	10
   	For Series S90 Auxiliary contact block for series S90 2CO	H5590ZW	555402	10
	Disconnect inhibitor for series S90, 3-pole to lock the mcb from disconnecting	AST	555681	10
	Actuation inhibitor for series S90, 3-pole to seal or inhibit the toggle in the open or closed state	BST	546243	6
	Busbar adapter for S90 1-pole (up to 63A)	SAV 91	546292	10
	Masking strip for lower meter wiring space lockable	VST	564549	10
	Accessory for N-connection S90 Ferrule 12/18mm, 300mm long, 2.5mm ²	ZE3 2.5	546294	1
Enclosure, grey	With base plate and mounting rail to DIN EN 50 022/05.78 sealable, protection degree IP20 1- or 2-pole	GH 1	546222	1
Enclosure, watertight	With base plate and mounting rail to DIN EN 50 022/05.78 sealable, protection degree IP54	LGW 4	546110	1