

SENSING & MONITORING RELAYS



TELE offers the widest range of products with the following performance features:

- Measurement of one or more quantities such as voltage, current, temperature and filling levels
- Internal or external power supply (e.g. 24 V DC)
- Monitor the voltage of ordinary mains grids at 230/400 V or 240/415 V as well as special industrial power supplies at 400/690 V
- Various forms of housing for control engineering, industrial systems and machine building as well as building installations; variants available for DIN rails, front installation or an 11-pole plug-in base

The robust design with generous terminal space throughout ensures very good usability and installability.

OVERVIEW

Page		
Monitoring Relays <i>WatchDog</i>	Introduction	10
Selection matrix	Quick, explicit and time-saving to the right product.	12
Function overview	Explanations of important terms	16
Industrial Series: GAMMA	- Voltage 3-phase - Voltage 1-phase - Current 1-phase - Current 3-phase - Temperature - Level	17 27 29 33 39 41
Industrial Series compact: DELTA	- Voltage 3-phase - Voltage 1-phase - Current 1-phase - Temperature - Level	49 53 55 57 59
Plugable Series: KAPPA	- Voltage 3-phase - Voltage 1-phase - Current 1-phase	61 61 61
Installation Series: ENYA	- Voltage 3-phase - Voltage 1-phase - Current 1-phase - Temperature - Level	63 63 77 79 81

WELCOME TO THE WORLD OF THE WATCHDOGS

The monitoring relays with the WatchDog label can display electrical values such as current, voltage, power factor, power performance, conductivity, resistance, temperature etc., meaning these can be monitored based on a limit value and deviations displayed on a message contact.

The housing is already a sign that the system has a robust design. The overvoltage category is consistently indicated with 3 so that industrial network environments do not present a problem. With the disruptive influences burst and surge, the normative requirements are more than fulfilled. The operating safety of

the devices is thus ensured even with high disruption potential. One difference that makes a difference. The temperature range in which the devices can be operated is between -25°C and +55°C.

The spacious operating front permits the accommodation of many setting options and display elements. A clear display with a separate LED for each operating mode is thus possible. There is only one rule here, and this has been valid with TELE for years: flashing LED means 'time running', continuously illuminated LED means 'time expired'. The operating elements have a flush arrangement in the

front, whereby up to 5 setting elements are possible in a 22.5 mm construction width. This permits maximum functionality on minimum space. As supply variants for the auxiliary voltage, CoolZoom with 24-240VAC/DC or the power modules with nominal voltages of up to 400V(TR2) or 500V(TR3) are available.

The Watchdogs are now also being used in the installation construction form thanks to the ENYA series. With up to 5 setting elements, an excellent operating comfort can be reached in this construction form too that is supplemented by up to four display elements.

These can also serve as a diagnosis

display in ongoing operation, in order to e.g. recognise in which phase the breakdown has occurred. ENYA devices can fit in every energy distribution cabinet and are thus ideally suited for use in building automation and control systems. They can be used to protect against an unwanted operating status, the detection of consumption points that are switched on or for classical control tasks. The application areas range from the monitoring of a four-wire network via one-phase monitoring applications to DC monitoring of battery-buffered systems. A diversity of current and voltage monitoring relays in one- and three-phase design are

available. The supply with these devices is integrated into the measuring circuit to save clamp connections.




coolZoom

The components mounted in a switching cabinet lead in total to a substantial heat development that has a negative impact on the lifecycle of the entire control unit. Through the use of state-of-the-art switching power supply technology, TELE reduces the energy consumption and thus also the heat development. The typical power consumption of the new products thus lies below the 1W mark – simply 'cool'. The lower operating temperature firstly has a positive effect on the lifecycle and reliability of the components and secondly results in substantial savings potential in the switching cabinet air climate control system and ventilation. Another benefit is demonstrated in the use of products in battery-buffered systems. Due to the lower power consumption, the battery

can be designed in a smaller size with extended follow-up time. With their extreme adaptability (zoom) to any voltage supply

in the range of 24 to 240VAC/DC, generous tolerance ranges (20.4 to 264VAC or 19.2 to 300VDC) and their usage options in the frequency range of 16 2/3 to 400Hz, the devices from TELE are suitable for any conceivable application.




PowerModules

In a simple and cost-effective manner, you adapt the WatchDog monitoring relays and load sentinels and the timing relays of the GAMMA series to the respective supply voltage. The plug-in power modules TR2 and TR3 are available for this and they only have to be inserted into the lateral supply slot of the devices.



The power modules TR2, with selectable nominal voltages of 12 to 440VAC, are envisaged for designs in 22.5mm construction width, while the power modules TR3 with nominal voltages of up to 500 V are suitable for types with a 45-mm wide housing. The supply voltage can therefore also be taken up by the outer conductor voltage if a neutral cable is not necessary in the application. The power modules work particularly 'quietly' in the

network, which means they are entirely suited for class B applications according to EN 55011 (living area). Another advantage: In the event of maintenance, the plug-in power module can be quickly and conveniently replaced. You simply order the right plug-in power modules for your application separately.



SERIES

Design



SENSING & MONITORING RELAYS



Type	Supply voltage	Measured range	Output
G4PM690VSYL20	12 - 440V AC, 24V DC ¹⁾	3(N)~ 400/690V AC (48 - 63Hz)	
G4PM500VSYL20	12 - 440V AC, 24V DC ¹⁾	3(N)~ 500V AC (48 - 63Hz)	
G2PM400VSY20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	3(N)~ 230/400V AC (48 - 63Hz)	
G2PM400VSY20	12 - 440V AC, 24V DC ¹⁾	3(N)~ 230/400V AC (48 - 63Hz)	
G2PM400VSY10	12 - 440V AC, 24V DC ¹⁾	3(N)~ 230/400V AC (48 - 63Hz)	
G2PM230VSY20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	3(N)~ 132/230V AC (48 - 63Hz)	
G2PM230VSY10	12 - 440V AC, 24V DC ¹⁾	3(N)~ 132/230V AC (48 - 63Hz)	
G2PM115VSY20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	3(N)~ 66/115V AC (48 - 63Hz)	
G2PM115VSY10	12 - 440V AC, 24V DC ¹⁾	3(N)~ 66/115V AC (48 - 63Hz)	
G2PW400V10	12 - 440V AC, 24V DC ¹⁾	3- 230/400V AC (48 - 63Hz)	
G2PU690VS20	3- 177 - 794V AC	3- 208 - 690V AC (48 bis 63Hz)	
G2PU400VSY10 230V AC	230V AC	3(N)~ 230/400V AC (48 - 63Hz)	
G2YM400VL20	12 - 440V AC, 24V DC ¹⁾	3N- 230/400V AC (16,6 - 400Hz)	
G2PF400VS02	3(N)- 342 - 457V AC	3(N)~ 230/400V AC (48 - 63Hz)	
G2PF230VS02	3(N)- 198 - 264V AC	3(N)~ 132/230V AC (48 - 63Hz)	
G2PF115VS02	3(N)- 99 - 132V AC	3(N)~ 66/115V AC (48 - 63Hz)	
G2FW400VL20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾		
G2UM500VL10 230V	230V AC	150V; 300V; 500V AC/DC (16,6 - 400Hz)	
G2UM300VL20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	30V; 60V; 300V AC/DC (16,6 - 400Hz)	
G2UM300VL20	12 - 440V AC, 24V DC ¹⁾	30V; 60V; 300V AC/DC (16,6 - 400Hz)	
G2UM300VL10	12 - 440V AC, 24V DC ¹⁾	30V; 60V; 300V AC/DC (16,6 - 400Hz)	
G2UM10VL20 24-240V AC/DC	24 - 240V AC/DC; CoolZoom ²⁾	60mV; 150mV; 10V AC/DC (16,6 - 400Hz)	
G2UW300V10	12 - 440V AC, 24V DC ¹⁾	30V; 60V; 300V AC/DC (48 - 63Hz)	
G2IM10AL20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	100mA; 1A; 10AAC/DC (16,6 - 400Hz)	
G2IM10AL20	12 - 440V AC, 24V DC ¹⁾	100mA; 1A; 10AAC/DC (48 - 63Hz)	

Functions	Spannung	3-phäsig	1-phäsig
Over (OVER)			
Under (UNDER)			
Window (WIN)			
Reverse Window			
Phase sequence (SEQ)			
Phase failure			
Asymmetry (ASYM)			
Fault latch (LATCH)			
Adjustable thresholds			
Adjustable hysteresis			
Start-up suppression (START)			
Tripping delay (DELAY)			
On delay (ON DELAY)			
Testfunction (TEST/RESET)			
Short circuit monitoring			
Zero-voltage latch			


Type	Supply voltage	Measured range	Output
G2IM10AL10	12 - 440V AC, 24V DC ¹⁾	100mA; 1A; 10AAC/DC (16,6 - 400Hz)	
G2IM5AL20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	20mA; 1A; 5AAC/DC (16,6 - 400Hz)	
G2IM5AL20	12 - 440V AC, 24V DC ¹⁾	20mA; 1A; 5AAC/DC (16,6 - 400Hz)	
G2IM5AL10	12 - 440V AC, 24V DC ¹⁾	20mA; 1A; 5AAC/DC (16,6 - 400Hz)	
G2IM2AL20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	800mA; 1,5A; 2AAC/DC (16,6 - 400Hz)	
G2IO10A10	12 - 440V AC, 24V DC ¹⁾	100mA; 1A; 10AAC/DC (48 - 63Hz)	
G2IO5A10	12 - 440V AC, 24V DC ¹⁾	20mA; 1A; 5AAC/DC (48 - 63Hz)	
G2IU10A10	12 - 440V AC, 24V DC ¹⁾	100mA; 1A; 10AAC/DC (48 - 63Hz)	
G2IU5A10	12 - 440V AC, 24V DC ¹⁾	20mA; 1A; 5AAC/DC (48 - 63Hz)	
G2JM5AL20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	3- 5A AC (48 - 63Hz)	
G2JM5AL20	12 - 440V AC, 24V DC ¹⁾	3- 5A AC (48 - 63Hz)	
G2TMTPT100L20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	PT100 2-/3-wire connection -50°C +200°C	
G2TFKN02 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	ΣR <1,5kΩ PTC (motortemperatur)	
G2TFKN02	12 - 440V AC, 24V DC ¹⁾	ΣR <1,5kΩ PTC (motortemperatur)	
G2TF02 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	ΣR <1,5kΩ PTC (motortemperatur)	
G2TF02	12 - 440V AC, 24V DC ¹⁾	ΣR <1,5kΩ PTC (motortemperatur)	
G2TF02 230V AC	230V AC	ΣR <1,5kΩ PTC (motortemperatur)	
G2TF02 110V AC	110V AC	ΣR <1,5kΩ PTC (motortemperatur)	
G2TF01	12 - 440V AC, 24V DC ¹⁾	ΣR <1,5kΩ PTC (motortemperatur)	
G2TF01 230V AC	230V AC	ΣR <1,5kΩ PTC (motortemperatur)	
G2LM20 24V AC	24V AC	0,25 - 100kΩ (conductiv probe)	
G2LM20 110V AC	110V AC	0,25 - 100kΩ (conductiv probe)	
G2LM20 230V AC	230V AC	0,25 - 100kΩ (conductiv probe)	

Functions	Strom	3-phäsig	Temperatur	Füllstand
Over (OVER)				
Under (UNDER)				
Window (WIN)				
Reverse Window				
Phase sequence (SEQ)				
Phase failure				
Asymmetry (ASYM)				
Fault latch (LATCH)				
Adjustable thresholds				
Adjustable hysteresis				
Start-up suppression (START)				
Tripping delay (DELAY)				
On delay (ON DELAY)				
Testfunction (TEST/RESET)				
Short circuit monitoring				
Zero-voltage latch				

Type	Supply voltage	Measured range	Output
G2IM10AL10	12 - 440V AC, 24V DC ¹⁾	100mA; 1A; 10AAC/DC (16,6 - 400Hz)	
G2IM5AL20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	20mA; 1A; 5AAC/DC (16,6 - 400Hz)	
G2IM5AL20	12 - 440V AC, 24V DC ¹⁾	20mA; 1A; 5AAC/DC (16,6 - 400Hz)	
G2IM5AL10	12 - 440V AC, 24V DC ¹⁾	20mA; 1A; 5AAC/DC (16,6 - 400Hz)	
G2IM2AL20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	800mA; 1,5A; 2AAC/DC (16,6 - 400Hz)	
G2IO10A10	12 - 440V AC, 24V DC ¹⁾	100mA; 1A; 10AAC/DC (48 - 63Hz)	
G2IO5A10	12 - 440V AC, 24V DC ¹⁾	20mA; 1A; 5AAC/DC (48 - 63Hz)	
G2IU10A10	12 - 440V AC, 24V DC ¹⁾	100mA; 1A; 10AAC/DC (48 - 63Hz)	
G2IU5A10	12 - 440V AC, 24V DC ¹⁾	20mA; 1A; 5AAC/DC (48 - 63Hz)	
G2JM5AL20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	3- 5A AC (48 - 63Hz)	
G2JM5AL20	12 - 440V AC, 24V DC ¹⁾	3- 5A AC (48 - 63Hz)	
G2TMTPT100L20 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	PT100 2-/3-wire connection -50°C +200°C	
G2TFKN02 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	ΣR <1,5kΩ PTC (motortemperatur)	
G2TFKN02	12 - 440V AC, 24V DC ¹⁾	ΣR <1,5kΩ PTC (motortemperatur)	
G2TF02 24-240V	24 - 240V AC/DC; CoolZoom ²⁾	ΣR <1,5kΩ PTC (motortemperatur)	
G2TF02	12 - 440V AC, 24V DC ¹⁾	ΣR <1,5kΩ PTC (motortemperatur)	
G2TF02 230V AC	230V AC	ΣR <1,5kΩ PTC (motortemperatur)	
G2TF02 110V AC	110V AC	ΣR <1,5kΩ PTC (motortemperatur)	
G2TF01	12 - 440V AC, 24V DC ¹⁾	ΣR <1,5kΩ PTC (motortemperatur)	
G2TF01 230V AC	230V AC	ΣR <1,5kΩ PTC (motortemperatur)	
G2LM20 24V AC	24V AC	0,25 - 100kΩ (conductiv probe)	
G2LM20 110V AC	110V AC	0,25 - 100kΩ (conductiv probe)	
G2LM20 230V AC	230V AC	0,25 - 100kΩ (conductiv probe)	

SERIES


Design



**SENSING &
MONITORING**

RELAYS


	Type	Supply voltage	Output	Functions
	Measured range			
E3YF400V02_0.85	= measured range	3N~ 230/400V AC (48 - 63Hz)	■	■
E3YF400VE20_0.85	= measured range	3N~ 230/400V AC (48 - 63Hz)	■	■
E3YF400VT02_0.85	= measured range	3N~ 230/400V AC (48 - 63Hz)	■	■
E3YF400VT02_HTV_0.85	= measured range	3N~ 230/400V AC (48 - 63Hz)	■	■
E1YF400V01_0.85	= measured range	3N~ 230/400V AC (48 - 63Hz)	■	■
E1YF400VT01_0.85	= measured range	3N~ 230/400V AC (48 - 63Hz)	■	■
E1YF400V01_0.70	= measured range	3N~ 230/400V AC (48 - 63Hz)	■	■
E3YM230VS20	= measured range	3(N)~ 132/230V AC (48 - 63Hz)	■	■
E1YM400VS10	= measured range	3(N)~ 230/400V AC (48 - 63Hz)	■	■
E1YM480Y/277VS10	= measured range	3~ 277/480V AC (48 - 63Hz)	■	■
E3YU400V02	= measured range	3(N)~ 230/400V AC (48 - 63Hz)	■	■
E1YU400V01	= measured range	3(N)~ 230/400V AC (48 - 63Hz)	■	■
E3YF400VFAL02	= measured range	3(N)~ 230/400V AC (48 - 63Hz)	■	■
E3PF400VSY02	= measured range	3(N)~ 230/400V AC (48 - 63Hz)	■	■
E1PF400VSY01	= measured range	3(N)~ 230/400V AC (48 - 63Hz)	■	■
E1PF480Y/277VSY10	= measured range	3~ 277/480V AC (48 - 63Hz)	■	■
E1UM230V01	= measured range	24V AC/DC; 230V AC (48 - 63Hz)	■	■
E1UU230V01	= measured range	24V AC/DC; 230V AC (48 - 63Hz)	■	■
E3M10AL20	230V AC	100mA; 1A; 10AAC/DC (16.6 - 400Hz)	■	■
E1IM10AACL10	230V AC	10AAC (48 - 63Hz)	■	■
E1IU5AAC01	230V AC	5AAC (48 - 63Hz)	■	■
E1IU500mAAC01	230V AC	500mA AC (48 - 63Hz)	■	■
E3TF01	230V AC	PTC (motor/temperature) $\Sigma R < 1.5k\Omega$	■	■
E3LM10	230V AC	0.25 - 100k Ω (conductiv probe)	■	■



FUNCTIONS-OVERVIEW


OVER

The output relay remains switched on until the monitored value exceeds the maximum value. As soon as the monitored value falls below the minimum value, the output relay switches to the on position again.




WIN

The output relay remains switched on until the monitored value lies within the defined window. As soon as the monitored value enters the defined window again, the output relay switches to the on position again.




UNDER

The output relay remains switched on until the monitored value falls below the minimum value. As soon as the monitored value exceeds the maximum value, the output relay switches to the on position again.




DELAY

If the monitored value leaves the selected range, the output relay only switches to the off position following expiry of the trip delay.



ON-DELAY

The output relay switches on if the monitored value is within the selected range during the defined time period.




LATCH (Fault latch)

If the device detects a fault, the output relay only switches on again when the fault latch has been reset. The fault latch can be reset by means of an internal or external reset button or by interrupting the supply voltage.



START-UP

The output relay switches on when the supply voltage is applied. Changes to measured variables have no impact on the setting of the output relay during start-up suppression.



I=0 Detection

Deactivated consumers are detected with I=0 detection. As soon as the current flow is supplied again, the measurement cycle commences again with the expiry of the defined start-up suppression.





Sensing & Monitoring Relays Series GAMMA




Voltage monitoring in 3-phase mains



- Multifunction
- Monitoring of phase sequence and phase failure
- Asymmetry detection switchable
- Connection of neutral wire optional
- Detection of loss of neutral wire
- Fault latch (G4PM)
- Supply voltage selectable via PowerModules or by zoom voltage 24 to 240V AC/DC
- 1 CO contact; 2 CO contacts
- Width 22,5mm or 45mm; Industrial design

types	G4PM690VSYL20	G4PM500VSYL20	G2PM400VSY20 24-240V	G2PM400VSY20	G2PM400VSY10
Art.No. (PQ1)	2394500	2394501	2390505	2390504	2390500
Art.No. (PQ10)	-	-	-	-	-
EAN13-Code	900866200296	900866200297	900866200284	900866200281	900866200276
Measured variable	3(N)~ AC Sinus (48 to 63Hz)	3(N)~ AC Sinus (48 to 63Hz)	3(N)~ AC Sinus (48 to 63Hz)	3(N)~ AC Sinus (48 to 63Hz)	3(N)~ AC Sinus (48 to 63Hz)
Measured range	$U_N = 690/400V$ terminals (N)-L1-L2-L3	$U_N = 500V$ terminals (N)-L1-L2-L3	$U_N = 400/230V$ terminals (N)-L1-L2-L3	$U_N = 400/230V$ terminals (N)-L1-L2-L3	$U_N = 400/230V$ terminals (N)-L1-L2-L3
Controls	ASYM • max • min • Delay • Function	ASYM • max • min • Delay • Function	ASYM • max • min • Delay • Function	ASYM • max • min • Delay • Function	ASYM • max • min • Delay • Function
Indicators (LEDs)	ASYM • max • min • SEQ • R	ASYM • max • min • SEQ • R	ASYM • max • min • SEQ • R	ASYM • max • min • SEQ • R	ASYM • max • min • SEQ • R
Functions	UNDER UNDER+SEQ WIN WIN+SEQ UNDER+LATCH UNDER+SEQ+LATCH WIN+LATCH WIN+SEQ+LATCH	UNDER UNDER+SEQ WIN WIN+SEQ UNDER+LATCH UNDER+SEQ+LATCH WIN+LATCH WIN+SEQ+LATCH	UNDER UNDER+SEQ WIN WIN+SEQ	UNDER UNDER+SEQ WIN WIN+SEQ	UNDER UNDER+SEQ WIN WIN+SEQ
Asymmetry	5% to 25% • Off	5% to 25% • Off	5% to 25% • Off	5% to 25% • Off	5% to 25% • Off
Switching threshold max.	-20% to 30% from U_N	-20% to 30% from U_N	-20% to 30% from U_N	-20% to 30% from U_N	-20% to 30% from U_N
Switching threshold min.	-30% to 20% from U_N	-30% to 20% from U_N	-30% to 20% from U_N	-30% to 20% from U_N	-30% to 20% from U_N
Tripping delay	0,1s to 10s	0,1s to 10s	0,1s to 10s	0,1s to 10s	0,1s to 10s
Start-up suppression time	-	-	-	-	-
Fault latch	selectable	selectable	-	-	-
Supply	PowerModule TR3 terminals A1-A2	PowerModule TR3 terminals A1-A2	24 to 240V AC/DC terminals A1-A2	PowerModule TR2 terminals A1-A2	PowerModule TR2 terminals A1-A2
Output	2 CO contacts; 250V, 5AAC	2 CO contacts; 250V, 5AAC	2 CO contacts; 250V, 5AAC	2 CO contacts; 250V, 5AAC	1 CO contact; 250V, 5AAC
Width	45mm	45mm	22,5mm	22,5mm	22,5mm
Certificates	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST
Mechanical design	Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm				
Terminal capacity	1 x 0,5 to 2,5mm ² with/without multicore cable end • 1 x 4mm ² without multicore cable end • 2 x 0,5 to 1,5mm ² with/without multicore cable end • 2 x 2,5mm ² flexible without multicore cable end				
Ambient conditions	Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)				
Accessories	PowerModulees TR2 (12 - 400V AC) and TR3 (12 - 500V AC) • sealable intervention protection shield FA-G2 • DC power supply SNT2 24VDC				

UNDER	Undervoltage monitoring
UNDER+SEQ	Undervoltage monitoring and monitoring of phase sequence
WIN	Monitoring the window between Min and Max
WIN+SEQ	Monitoring the window between Min and Max and monitoring of phase sequence
UNDER+Latch	Undervoltage monitoring with fault latch
UNDER+SEQ+Latch	Undervoltage monitoring and monitoring of phase sequence with fault latch
WIN+Latch	WIN with fault latch
WIN+SEQ+Latch	Monitoring the window between Min and Max and monitoring of phase sequence with fault latch



Functions

Sensing & Monitoring Relays Series GAMMA *WatchDog*



Voltage monitoring in 3-phase mains

- Multifunction (G2PM); Windowfunction (G2PW)
- Monitoring of phase sequence and phase failure (G2PM)
- Asymmetry detection switchable (G2PM)
- Connection of neutral wire optional (G2PM)
- Detection of loss of neutral wire (G2PM)
- Supply voltage selectable via PowerModules or by zoom voltage 24-240V
- 1 CO contact; 2 CO contacts
- Width 22,5mm
- Industrial design

Connections


types	G2PM230VSY20 24-240V	G2PM230VSY10	G2PM115VSY20 24-240V	G2PM115VSY10	G2PW400V10
Art.No. (PQ1)	2390512	2390503	2390506	2390502	2390501
Art.No. (PQ10)	-	-	-	-	-
EAN13-Code	900866200287	900866200280	900866200516	900866200279	900866200277
Measured variable	3(N)~ AC Sinus (48 to 63Hz)	3(N)~ AC Sinus (48 to 63Hz)	3(N)~ AC Sinus (48 to 63Hz)	3(N)~ AC Sinus (48 to 63Hz)	3~ AC Sinus (48 to 63Hz)
Measured range	$U_n = 230/132V$ terminals (N)-L1-L2-L3	$U_n = 230/132V$ terminals (N)-L1-L2-L3	$U_n = 115/66V$ terminals (N)-L1-L2-L3	$U_n = 115/66V$ terminals (N)-L1-L2-L3	$U_n = 400/230V$ terminals L1-L2-L3
Controls	ASYM • max • min • Delay • Function	ASYM • max • min • Delay • Function	ASYM • max • min • Delay • Function	ASYM • max • min • Delay • Function	max • min • Delay
Indicators (LEDs)	ASYM • max • min • SEQ • R	ASYM • max • min • SEQ • R	ASYM • max • min • SEQ • R	ASYM • max • min • SEQ • R	U • max • min • R
Functions	UNDER UNDER+SEQ WIN WIN+SEQ	UNDER UNDER+SEQ WIN WIN+SEQ	UNDER UNDER+SEQ WIN WIN+SEQ	UNDER UNDER+SEQ WIN WIN+SEQ	WIN
Asymmetry	5% to 25% • Off	5% to 25% • Off	5% to 25%	5% to 25% • Off	-
Switching threshold max.	-20% to 30% from U_n	-20% to 30% from U_n	-20% to 30% from U_n	-20% to 30% from U_n	-20% to 30% from U_n
Switching threshold min.	-30% to 20% from U_n	-30% to 20% from U_n	-30% to 20% from U_n	-30% to 20% from U_n	-30% to 20% from U_n
Tripping delay	0,1s to 10s	0,1s to 10s	0,1s to 10s	0,1s to 10s	0,2s to 10s
Start-up suppression time	-	-	-	-	-
Fault latch	-	-	-	-	-
Supply	24 to 240V AC/DC terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2	24 to 240V AC/DC terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2
Output	2 CO contacts 250V, 5A AC	1 CO contact 250V, 5A AC	2 CO contacts 250V, 5A AC	1 CO contact 250V, 5A AC	1 CO contact 250V, 5A AC
Width	22,5mm	22,5mm	22,5mm	22,5mm	22,5mm
Certificates	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST
Mechanical design	Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm				
Terminal capacity	1 x 0,5 to 2,5mm ² with/without multicore cable end • 1 x 4mm ² without multicore cable end • 2 x 0,5 to 1,5mm ² with/without multicore cable end • 2 x 2,5mm ² flexible without multicore cable end				
Ambient conditions	Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)				
Accessories	PowerModule TR2 (12 - 440V AC) • DC power supply SNT2 24V DC • sealable intervention protection shield FA-G2				

Dimensions


UNDER
UNDER+SEQ
WIN
WIN+SEQ

Undervoltage monitoring
Undervoltage monitoring and monitoring of phase sequence
Monitoring the window between Min and Max
Monitoring the window between Min and Max and monitoring of phase sequence


G2PM with PowerModule 24V AC




G2PM with PowerModule 230VAC



G2PM with PowerModule 400VAC



Width 22,5mm



Functions



Sensing & Monitoring Relays Series GAMMA

WatchDog

Voltage monitoring in 3-phase mains

- Multifunction (G2PM); Windowfunction
- Monitoring of phase sequence and phase failure
- Asymmetry detection switchable
- Connection of neutral wire optional
- Detection of loss of neutral wire
- Supply voltage selectable via PowerModules or by zoom voltage 24-240V
- 1 CO contact; 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

types

G2PU690VS20



G2PU400VSY10
230V AC



2390507

2390511B

9008662006454

9008662006652

3~
AC Sinus (48 bis 63Hz)

3(N)~
AC Sinus (48 to 63Hz)

208V to 690V
terminals L1-L2-L3

U_N = 400/230V
terminals (N)-L1-L2-L3

min • Delay

ASYM • max • min

U • min • SEQ • R

ASYM • max • min • SEQ • R

UNDER+SEQ

UNDER+SEQ

fixed, 25%

5% to 25%

-

-20% to +30% from U_N

180V to 690V

-30% to +20% from U_N

0,1s to 10s

-

-

-

= measuring voltage
3~ 177V to 794V
Terminals L1-L2-L3

230V AC
terminals A1-A2

2 CO contacts
250V, 5A AC

1 CO contact
250V, 5A AC

22,5mm

22,5mm

CE • GOST

CE • cULus • GOST

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any •

Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end

• 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)

Sealable intervention protection shield FA-G2

Dimensions

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Controls

Indicators (LEDs)

Functions

Asymmetry

Switching threshold max.

Switching threshold min.

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity


Ambient conditions

Accessories




G2PU400VSY10, supply voltage 230V AC

G2PU690VS20



Width 22,5mm



Functions



Sensing & Monitoring Relays Series GAMMA

WatchDog

Voltage monitoring in 3-phase mains



- Multifunction
- Monitors phase to neutral voltages
- Connection of neutral wire necessary
- Fault latch
- Supply voltage selectable via PowerModules or DC power supply
- 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

types

G2YM400VL20



2390508

-

900866200285

3N~

AC Sinus (16 to 400Hz)

Ui = 400/230V

terminals N-L1-L2-L3

max • min • Delay • Function

U • max • min • R

OVER

OVER+LATCH

UNDER

UNDER+LATCH

WIN

WIN+LATCH

-

-20% to 30% from UN

-30% to 20% from UN

0,1s to 10s

selectable

PowerModule TR2 or SNT2

terminals A1-A2

2 CO contacts

250V, 5A AC

22,5mm

CE • cULus • GOST

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Controls

Indicators (LEDs)

Functions

Asymmetry

Switching threshold max.

Switching threshold min.

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design


Terminal capacity

Ambient conditions


Accessories

OVER	Overvoltage monitoring
OVER+Latch	Overvoltage monitoring with fault latch
UNDER	Undervoltage monitoring
UNDER+Latch	Undervoltage monitoring with fault latch
WIN	Monitoring the window between Min and Max
WIN+Latch	Monitoring the window between Min and Max with fault latch


G2YM400VL20 with PowerModule 24V AC without fault latch




G2YM400VL20 with PowerModule 230V AC with fault latch



G2YM400VL20 with PowerModule 230V AC without fault latch



Width 22,5mm



Functions



Sensing & Monitoring Relays Series GAMMA

WatchDog

Voltage monitoring in 3-phase mains

- Monitoring of phase sequence and phase failure
- Detection of reverse voltage
- Connection of neutral wire optional
- Supply voltage = measuring voltage
- 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

types

G2PF400VS02

G2PF230VS02

G2PF115VS02



Connections

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Controls

Indicators (LEDs)

Functions

Asymmetry

Switching threshold max.

Switching threshold min.

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

2390000

2390000B

900866200229

3(N)~
AC Sinus (48 to 63Hz)U_N = 400/230V
terminals (N)-L1-L2-L3

-

U • R

Monitoring of phase sequence and phase failure

fixed, typ. 30%

-

-

fixed, max. 350ms

fixed, max. 500ms

-

= measuring voltage
3(N)- 342 to 457V
terminals (N)-L1-L2-L32 CO contacts
250V, 5AAC

22,5mm

CE • cULus • GOST

2390001

-

900866200232

3(N)~
AC Sinus (48 to 63Hz)U_N = 230/132V
terminals (N)-L1-L2-L3

-

U • R

Monitoring of phase sequence and phase failure

fixed, typ. 30%

-

-

fixed, max. 350ms

fixed, max. 500ms

-

= measuring voltage
3(N)- 198 to 264V
terminals (N)-L1-L2-L32 CO contacts
250V, 5AAC

22,5mm

CE • cULus • GOST

2390002

-

900866200234

3(N)~
AC Sinus (48 to 63Hz)U_N = 115/66V
terminals (N)-L1-L2-L3

-

U • R

Monitoring of phase sequence and phase failure

fixed, typ. 30%

-

-

fixed, max. 350ms

fixed, max. 500ms

-

= measuring voltage
3(N)- 99 to 132V
terminals (N)-L1-L2-L32 CO contacts
250V, 5AAC

22,5mm

CE • cULus • GOST

•

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm


1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)


-



G2PF...S02



Width 22,5mm



Functions

- Window function
- Measured voltage 110V to 400V
- Error memory
- Voltage breakdown detection
- Supply voltage 24 to 240V AC/DC
- 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

types

G2FW400VL20 24-240V



Dimensions

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Controls

Indicators (LEDs)

Functions

Switching threshold max.

Switching threshold min.

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

2390900

9008662006607

Frequency, 1-phae terminals F-E

110V to 400V terminals F-E

Start • max • min • Delay • Function

U/t • max • min • UFailure • R

WIN

 $F_N = 50\text{Hz}$: 49, 49, 5, 50, 50, 5, 51, 52, 53, 55, 57, 5, 60Hz
 $F_N = 60\text{Hz}$: 59, 59, 5, 60, 60, 5, 61, 62, 63, 65, 67, 5, 70Hz $F_N = 50\text{Hz}$: 40, 42, 5, 45, 47, 48, 49, 49, 5, 50, 50, 5, 51Hz
 $F_N = 60\text{Hz}$: 50, 52, 5, 55, 57, 58, 59, 59, 5, 60, 60, 5, 61Hz

0,1s to 10s

0s to 10s

24 to 240V AC/DC terminals A1-A2

2 CO contacts 250V, 5AAC

22,5mm

CE

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)

PowerModule TR2 (12 to 440V AC) • DC power supply SNT2 24V DC • sealable intervention protection shield FA-G2

G2FW400VL20 24-240V:

Frequency monitoring for 50/60Hz supply with adjustable thresholds, separately adjustable on delay and trip delay.

50Hz:

WIN: Window monitoring, monitoring of range..., $F_N=50\text{Hz}$


WIN+Latch: Window monitoring with error memory, $F_N=50\text{Hz}$

60Hz:


WIN: Window monitoring, monitoring of range..., $F_N=60\text{Hz}$

WIN+Latch: Window monitoring with error memory, $F_N=60\text{Hz}$

G2FW400VL20, measured voltage = 400V AC (phase-phase)
supply voltage 24-240V AC/DC



Width 22,5mm



Functions



Sensing & Monitoring Relays Series GAMMA

WatchDog



Voltage monitoring in 1-phase mains

- Multifunction
- Frequency range 16,6 to 400Hz
- Fault latch
- Supply voltage selectable via PowerModules or by zoom voltage 24 to 240V AC/DC
- 1 CO contact; 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

types

G2UM500VL10 230V

G2UM300VL20
24-240V AC

G2UM300VL20



Dimensions

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measuring ranges

Controls

Indicators (LEDs)

Functions

Switching threshold max.

Switching threshold min.

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

2390306A

2390304

2390303

900866200262

900866200260

900866200259

Voltage AC/DC
AC Sinus (16,6 to 400Hz)

Voltage AC/DC
AC Sinus (16,6 to 400Hz)

Voltage AC/DC
AC Sinus (16,6 to 400Hz)

150V; terminals E-F1(+)
300V; terminals E-F2(+)
500V; terminals E-F3(+)

30V; terminals E-F1(+)
60V; terminals E-F2(+)
300V; terminals E-F3(+)

30V; terminals E-F1(+)
60V; terminals E-F2(+)
300V; terminals E-F3(+)

Start • max • min • Delay • Function

Start • max • min • Delay • Function

Start • max • min • Delay • Function

U/t • max • min • R

U/t • max • min • R

U/t • max • min • R

OVER
OVER+LATCH
UNDER
UNDER+LATCH
WIN
WIN+LATCH

OVER
OVER+LATCH
UNDER
UNDER+LATCH
WIN
WIN+LATCH

OVER
OVER+LATCH
UNDER
UNDER+LATCH
WIN
WIN+LATCH

10% to 100% from U_N

10% to 100% from U_N

10% to 100% from U_N

5% to 95% from U_N

5% to 95% from U_N

5% to 95% from U_N

0,1s to 10s

0,1s to 10s

0,1s to 10s

0s to 10s

0s to 10s

0s to 10s

selectable

selectable

selectable

230V AC
terminals A1-A2

24 to 240V AC/DC
terminals A1-A2

PowerModule TR2 or
SNT2
terminals A1-A2

1 CO contacts
250V, 5A AC

2 CO contacts
250V, 5A AC

2 CO contacts
250V, 5A AC

22,5mm

22,5mm

22,5mm

CE • cULus • GOST

CE • cULus • GOST

CE • cULus • GOST

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)

PowerModule TR2 (12 to 440V AC) • DC power supply SNT2 24V DC • sealable intervention protection shield FA-G2

OVER
UNDER
WIN

Overvoltage monitoring
UNDERvoltage monitoring
Monitoring the window between Min and Max




OVER+Latch
UNDER+Latch
WIN+Latch

Overvoltage monitoring with fault latch
UNDERvoltage monitoring with fault latch
Monitoring the window between Min and Max with fault latch


G2UM500VL10, measuring range: 300V
supply voltage: 230V AC

G2UM300VL20, measuring range: 300V
supply voltage: 24-240V AC/DC

G2UM300VL20, measuring range: 30V
supply voltage: 24V AC



Width 22,5mm



Functions



Sensing & Monitoring Relays Series GAMMA

WatchDog



Voltage monitoring in 1-phase mains

- Multifunction (G2UM); Windowfunction (G2UW)
- Frequency range 16,6 to 400Hz (G2UM)
- Fault latch (G2UM)
- Supply voltage selectable via PowerModules or by zoom voltage 24 to 240V AC/DC
- 1 CO contact; 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

types

G2UM300VL10

G2UM10VL20
24-240V AC/DC

G2UW300V10



Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measuring ranges

Controls

Indicators (LEDs)

Functions

2390300

-

900866200256

Voltage AC/DC
AC Sinus (16 to 400Hz)

30V; terminals E-F1(+)
60V; terminals E-F2(+)
300V; terminals E-F3(+)

Start • max • min • Delay • Function

U/t • max • min • R

OVER
OVER+LATCH
UNDER
UNDER+LATCH
WIN
WIN+LATCH

10% to 100% from U_N

5% to 95% from U_N

0,1s to 10s

0s to 10s

wire link Y1-Y2

PowerModule TR2 or SNT2
terminals A1-A2

1 CO contact
250V, 5A AC

22,5mm

CE • cULus • GOST

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm
1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end
• 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)

PowerModuleee TR2 (12 to 440V AC) • DC power supply SNT2 24V DC • sealable intervention protection shield FA-G2

Dimensions

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measuring ranges

Controls

Indicators (LEDs)

Functions

Switching threshold max.

Switching threshold min.

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

10% to 100% from U_N

5% to 95% from U_N

0,1s to 10s

0s to 10s

wire link Y1-Y2

PowerModule TR2 or SNT2
terminals A1-A2

1 CO contact
250V, 5A AC

22,5mm

CE • cULus • GOST

10% to 100% from U_N

5% to 95% from U_N

0,1s to 10s

0s to 10s

wire link Y1-Y2

PowerModule TR2 or SNT2
terminals A1-A2

2 CO contacts
250V, 5A AC

22,5mm

CE • cULus • GOST

10% to 100% from U_N

5% to 95% from U_N

0,1s to 10s

0s to 10s

wire link Y1-Y2

PowerModule TR2 or SNT2
terminals A1-A2

1 CO contact
250V, 5A AC

22,5mm

CE • cULus • GOST

10% to 100% from U_N

5% to 95% from U_N

0,2s to 10s

-

WIN

U • max • min • R

U • max • min • R

CE • cULus • GOST

CE • cULus • GOST

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm
1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end
• 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)

PowerModuleee TR2 (12 to 440V AC) • DC power supply SNT2 24V DC • sealable intervention protection shield FA-G2


OVER
UNDER
WIN

Overvoltage monitoring
UNDervoltage monitoring
Monitoring the window between Min and Max


G2UM

Fault latch via wire link Y1-Y2 selectable
OVER+Latch Overvoltage monitoring with fault latch
UNDER+Latch UNDervoltage monitoring with fault latch
WIN+Latch Monitoring the window between Min and Max with fault latch

G2UM300VL10, measuring range 60V AC/DC, supply voltage: 230V AC
G2UW300V10, measuring range 30V AC/DC, supply voltage: 24V AC
G2UM10VL20, measuring range: 60mV AC/DC, supply voltage: 24V AC/DC



Width 22,5mm



Functions

- Multifunction
- Frequency range 16,6 to 400Hz
- Fault latch
- Supply voltage selectable via PowerModules or by zoom voltage 24 to 240V AC/DC
- 1 CO contact; 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

types	G2IM10AL20 24-240V	G2IM10AL20 24-240V	G2IM10AL10 24-240V	G2IM5AL20 24-240V
Art.No. (PQ1)	2390410	2390406	2390400	2390411
Art.No. (PQ10)	-	-	-	-
EAN13-Code	900866200273	900866200269	900866200263	900866200274
Measured variable	Current AC/DC AC Sinus (16,6 to 400Hz)	Current AC/DC AC Sinus (16,6 to 400Hz)	Current AC/DC AC Sinus (16,6 to 400Hz)	Current AC/DC AC Sinus (16,6 to 400Hz)
Measuring ranges	100mA AC/DC; terminals K-1(+) 1A AC/DC; terminals K-2(+) 10A AC/DC; terminals K-3(+)	100mA AC/DC; terminals K-1(+) 1A AC/DC; terminals K-2(+) 10A AC/DC; terminals K-3(+)	100mA AC/DC; terminals K-1(+) 1A AC/DC; terminals K-2(+) 10A AC/DC; terminals K-3(+)	20mA AC/DC; terminals K-1(+) 1A AC/DC; terminals K-2(+) 5A AC/DC; terminals K-3(+)
Controls	Start • max • min • Delay • Function	Start • max • min • Delay • Function	Start • max • min • Delay • Function	Start • max • min • Delay • Function
Indicators (LEDs)	U/t • max • min • R	U/t • max • min • R	U/t • max • min • R	U/t • max • min • R
Functions	OVER OVER+LATCH UNDER UNDER+LATCH WIN WIN+LATCH	OVER OVER+LATCH UNDER UNDER+LATCH WIN WIN+LATCH	OVER OVER+Latch UNDER UNDER + Latch WIN WIN+Latch	OVER OVER+LATCH UNDER UNDER+LATCH WIN WIN+Latch
Switching threshold max.	10% to 100% from I _N	10% to 100% from I _N	10% to 100% from I _N	10% to 100% from I _N
Switching threshold min.	5% to 95% from I _N	5% to 95% from I _N	5% to 95% from I _N	5% to 95% from I _N
Tripping delay	0,1s to 10s	0,1s to 10s	0,1s to 10s	0,1s to 10s
Start-up suppression time	0s to 10s	0s to 10s	0s to 10s	0s to 10s
Fault latch	selectable	selectable	selectable	selectable
Supply	24 to 240V terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2	24 to 240V terminals A1-A2
Output	2 CO contacts 250V, 5A AC	2 CO contacts 250V, 5A AC	1 CO contact 250V, 5A AC	2 CO contacts 250V, 5A AC
Width	22,5mm	22,5mm	22,5mm	22,5mm
Certificates	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST
Mechanical design				
Terminal capacity				
Ambient conditions	1 x 0,5 to 2,5mm ² with/without multicore cable end • 1 x 4mm ² without multicore cable end • 2 x 0,5 to 1,5mm ² with/without multicore cable end • 2 x 2,5mm ² flexible without multicore cable end			
Accessories				

Sensing & Monitoring Relays Series GAMMA

WatchDog

Current monitoring in 1-phase mains




OVER
UNDER
WIN

Overcurrent monitoring
Undercurrent monitoring
Monitoring the window between Min and Max


OVER+Latch
UNDER+Latch
WIN+Latch

Overcurrent monitoring with fault latch
Undercurrent monitoring with fault latch
Monitoring the window between Min and Max with fault latch


Measured range 100mA AC/DC,
supply voltage: 24V AC/DC




Measured range 1A AC/DC with
Powermodule 230V AC



Measured range 5A AC/DC,
supply voltage: 24V AC/DC



Width 22,5mm



Functions



Sensing & Monitoring Relays Series GAMMA

WatchDog

Current monitoring in 1-phase mains



- Multifunction
- Frequency range 16,6 to 400Hz
- Fault latch
- Supply voltage selectable via PowerModules or by zoom voltage 24-240V
- 1 CO contact; 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

G2IM10AL20 24-240V
G2IM10L20
G2IM5AL20 24-240V

types

G2IM5AL20

G2IM5AL10

G2IM2AL20 24-240V



Dimensions

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measuring ranges

Controls

Indicators (LEDs)

Functions

Switching threshold max.

Switching threshold min.

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

2390405

-

900866200268

Current AC/DCAC Sinus (16,6 to 400Hz)

20mA AC/DC; terminals K-I1(+)1A AC/DC; terminals K-I2(+).5A AC/DC; terminals K-I3(+)

Start • max • min • Delay • Function

U/t • max • min • R

OVER

OVER+LATCH

UNDER

UNDER+LATCH

WIN

WIN+LATCH

10% to 100% from I_N

5% to 95% from I_N

0,1s to 10s

selectable

PowerModule TR2 or SNT2 terminals A1-A2

2 CO contacts250V, 5A AC

22,5mm

CE • cULus • GOST

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)

PowerModulee TR2 (12 to 440V AC) • DC power supply SNT2 24V DC • Current Transformers Series DSW and WSW • sealable intervention protection shield FA-G2

2390401

-

900866200264

Current AC/DC AC Sinus (16,6 to 400Hz)

20mA AC/DC; terminals K-I1(+)1A AC/DC; terminals K-I2(+).5A AC/DC; terminals K-I3(+)

Start • max • min • Delay • Function

U/t • max • min • R

OVER

OVER+Latch

UNDER

UNDER + Latch

WIN

WIN+Latch

10% to 100% from I_N

5% to 95% from I_N

0,1s to 10s

selectable

PowerModule TR2 or SNT2 terminals A1-A2

1 CO contact 250V, 5A AC

22,5mm

CE • cULus • GOST

30% to 100% from I_N

25% to 95% from I_N

0,1s to 10s

selectable

24-240V terminals A1-A2

1 CO contact 250V, 5A AC

22,5mm

CE • cULus • GOST

24-240V terminals A1-A2

1 CO contact 250V, 5A AC

22,5mm

CE • cULus • GOST

24-240V terminals A1-A2


OVER
UNDER
WIN

Overcurrent monitoring
Undercurrent monitoring
Monitoring the window between Min and Max


OVER+Latch
UNDER+Latch
WIN+Latch

Overcurrent monitoring with fault latch
Undercurrent monitoring with fault latch
Monitoring the window between Min and Max with fault latch


Measuring range 20mA AC/DC,
supply voltage: 24V AC/DC




Measuring range 5A AC/DC with
Powermodule 400V AC



Measuring range 2A AC/DC,
supply voltage: 24V AC/DC



Width 22.5mm



Functions



Sensing & Monitoring Relays Series GAMMA

WatchDog

Current monitoring in 1-phase mains

- Overcurrent monitoring (G2IO)
- UNDERcurrent monitoring (G2IU)
- Supply voltage via PowerModules or DC power supply
- 1 CO contact
- Width 22,5mm
- Industrial design

Connections

G2IM5AL20
G2IM5AL10
G2IM2AL20 24-240V

Dimensions


Dimensions

types	G2IO10A10	G2IO5A10	G2IU10A10	G2IU5A10
Art.No. (PQ1)	2390408	2390403	2390409	2390404
Art.No. (PQ10)	-	-	-	-
EAN13-Code	900866200271	900866200266	900866200272	900866200267
Measured variable	Current AC/DC AC Sinus (48 to 63Hz)	Current AC/DCAC Sinus (48 to 63Hz)	Current AC/DC AC Sinus (48 to 63Hz)	Current AC/DC AC Sinus (48 to 63Hz)
Measuring ranges	100mA AC/DC; terminals K-I1(+) 1A AC/DC; terminals K-I2(+) 10A AC/DC; terminals K-I3(+)	20mA AC/DC; terminals K-I1(+) 1A AC/DC; terminals K-I2(+) 5A AC/DC; terminals K-I3(+)	100mA AC/DC; terminals K-I1(+) 1A AC/DC; terminals K-I2(+) 10A AC/DC; terminals K-I3(+)	20mA AC/DC; terminals K-I1(+) 1A AC/DC; terminals K-I2(+) 5A AC/DC; terminals K-I3(+)
Controls	max • min • Delay	max • min • Delay	max • min • Delay	max • min • Delay
Indicators (LEDs)	U • max • min • R	U • max • min • R	U • max • min • R	U • max • min • R
Functions	OVER	OVER	UNDER	UNDER
Switching threshold max.	10% to 100% from I_N	10% to 100% from I_N	10% to 100% from I_N	10% to 100% from I_N
Switching threshold min.	5% to 95% from I_N	5% to 95% from I_N	5% to 95% from I_N	5% to 95% from I_N
Tripping delay	0,2s to 10s	0,2s to 10s	0,2s to 10s	0,2s to 10s
Start-up suppression time	-	-	-	-
Fault latch	-	-	-	-
Supply	PowerModule TR2 or SNT2 terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2
Output	1 CO contact 250V, 5A AC	1 CO contact 250V, 5A AC	1 CO contact 250V, 5A AC	1 CO contact 250V, 5A AC
Width	22,5mm	22,5mm	22,5mm	22,5mm
Certificates	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST
Mechanical design	Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm			
Terminal capacity	1 x 0,5 to 2,5mm ² with/without multicore cable end • 1 x 4mm ² without multicore cable end • 2 x 0,5 to 1,5mm ² with/without multicore cable end • 2 x 2,5mm ² flexible without multicore cable end			
Ambient conditions	Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz, 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)			
Accessories	PowerModules TR2 (12 to 440V AC) • DC power supply SNT2 24V DC • Current Transformers Series DSW and WSW • sealable intervention protection shield FA-G2			


OVER
UNDER

Overcurrent monitoring
Undercurrent monitoring


Measured range 20mA with Powermodule 24V AC



Measured range 1A with Powermodule 230V AC



Width 22,5mm



Functions



Sensing & Monitoring Relays Series GAMMA

WatchDog



Current monitoring in 3-phase mains

- Multifunction
- Fault latch
- Supply voltage selectable via PowerModules or by zoom voltage 24 to 240V AC/DC
- 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

G2I05A10
G2IU5A10
G2IO10A10
G2IU10A10

types

G2JM5AL20 24-240V

G2JM5AL20



2390801

2390800

900866200294

900866200293

Current 3~
AC Sinus (48 to 63Hz)

Current 3~
AC Sinus (48 to 63Hz)

5AAC
terminals K-I1, K-I2, K-I3

5AAC
terminals K-I1, K-I2, K-I3

Start • max • min • Delay • Function

Start • max • min • Delay • Function

U/t • max • min • R

U/t • max • min • R

OVER
OVER+LATCH
UNDER
UNDER+LATCH
WIN
WIN+LATCH

OVER
OVER+LATCH
UNDER
UNDER+LATCH
WIN
WIN+LATCH

10% to 100% from IN

10% to 100% from I_N

5% to 95% from IN

5% to 95% from I_N

0,1s to 10s

0,1s to 10s

0s to 10s
selectable

0s to 10s
selectable

24 to 240V AC/DC
terminals A1-A2

PowerModule TR2 or SNT2
terminals A1-A2

2 CO contacts
250V, 5AAC

2 CO contacts
250V, 5AAC

22,5mm

22,5mm

CE • cULus • GOST

CE • cULus • GOST

Dimensions

Art.No. (PQ1)
Art.No. (PQ10)
EAN13-Code

Measured variable

Measured range

Controls
Indicators (LEDs)

Functions

Switching
threshold max.
Switching threshold min.

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical
design

Terminal capacity

Ambient
conditions


Accessories

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm
1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end
Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)


PowerModulees TR2 (12 to 440V AC) • DC power supply SNT2 24V DC • Current Transformers Series DSW and WSW • sealable intervention protection shield FA-G2

OVER	Overcurrent monitoring
OVER+LATCH	Overcurrent monitoring with fault latch
UNDER	Undercurrent monitoring
UNDER+LATCH	Undercurrent monitoring with fault latch
WIN	Monitoring the window between Min and Max
WIN+LATCH	Monitoring the window between Min and Max with fault latch


G2JM5AL20, Supply 230V AC and Current Transformers



G2JM5AL20, Supply 230V AC and fault latch



Width 22,5mm



Functions

Sensing & Monitoring Relays Series GAMMA **WatchDog**

Temperature monitoring

- Temperature monitoring by PT100 probes (2- and 3-wire connection)
- Multifunction
- Monitoring of short circuit or line break of sensor line
- Fault latch
- Supply voltage by zoom voltage 24 to 240V AC/DC
- 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

types

G2TMPT100L20 24-240V



2390904

-

900866200295

Temperature monitoring PT100
2- and 3-wire connection-50°C to +200°C
terminals T1-T2-T3

Start • max • min • Offset • Function

U/t • max • min • Sense • R

OVER

OVER+LATCH

UNDER

UNDER+LATCH

WIN

WIN+LATCH

-45°C to +200°C

-50°C to 195°C

-

0min to 30min

selectable

24 to 240V AC/DC
terminals A1-A22 CO contacts
250V, 5A AC

22,5mm

CE • cULus • GOST

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)

Sealable intervention protection shield FA-G2

Dimensions

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Controls

Indicators (LEDs)

Functions

Switching threshold max.

Switching threshold min.

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity


Ambient conditions

Accessories


OVER
OVER+LATCH
UNDER
UNDER+LATCH
WIN
WIN+LATCH

Monitoring of overtemperature
Monitoring of overtemperature with fault latch
Monitoring of undertemperature
Monitoring of undertemperature with fault latch
Monitoring the window between Min and Max
Monitoring the window between Min and Max with fault latch


2-wire connection, Supply 24V AC/DC and fault latch



3-wire connection, Supply 230V AC without fault latch



Width 22,5mm



Functions



Sensing & Monitoring Relays Series GAMMA

WatchDog




Temperature monitoring

- Temperature monitoring of the motor winding in accordance with DIN 44081
- Maximal 6 PTC probes
- Fault latch
- Short circuit monitoring of the PTC Input (G2TFKN02)
- Testfunction with integrated Test/Reset button; possibility for external reset
- Supply voltage selectable via PowerModules or by zoom voltage 24 to 240VAC/DC
- 1 CO contact; 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

types

G2TFKN02
24-240V G2TFKN02
G2TF02 24-240V G2TF02




Dimensions

Art.No. (PQ1)	2390110	2390101	2390111	2390100
Art.No. (PQ10)				
EAN13-Code	900866200251	900866200237	900866200252	900866200236
Measured variable	PTC (motortemperature) max. 6 PTC probes	PTC (motortemperature) max. 6 PTC probes	PTC (motortemperature) max. 6 PTC probes	PTC (motortemperature) max. 6 PTC probes
Measured range	total resistance cold <1,5kΩ terminals T1-T2	total resistance cold <1,5kΩ terminals T1-T2	total resistance cold <1,5kΩ terminals T1-T2	total resistance cold <1,5kΩ terminals T1-T2
Measuring voltage	≤2,5V DC at R >4,0kΩ (DINVDE 0660 part 302)	≤2,5V DC at R >4,0kΩ (DINVDE 0660 part 302)	≤2,5V DC at R >4,0kΩ (DINVDE 0660 part 302)	≤2,5V DC at R >4,0kΩ (DINVDE 0660 part 302)
Controls	Test/Reset button • Function	Test/Reset button • Function	Test/Reset button	Test/Reset button
Indicators (LEDs)	U • Failure • R	U • Failure • R	U • Failure	U • Failure
Functions	Overtemperature selectable functions: +K (short circuit monitoring) +N (remanent latch function) +K+N (short circuit monitoring and remanent latch function)	Overtemperature selectable functions: +K (short circuit monitoring) +N (remanent latch function) +K+N (short circuit monitoring and remanent latch function)	Overtemperature	Overtemperature
Response value	3,6kΩ	3,6kΩ	3,6kΩ	3,6kΩ
Release value	1,8kΩ	1,8kΩ	1,8kΩ	1,8kΩ
Short circuit monitoring	<20Ω	<20Ω	-	-
Fault latch	yes (auto)	yes (auto)	yes (auto)	yes (auto)
Reset	internal or external terminals R-T2	internal or external terminals R-T2	internal or external terminals R-T2	internal or external terminals R-T2
Supply	24 to 240V AC/DC terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2	24-240V AC/DC terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2
Output	2 CO contacts 250V, 5AAC	2 CO contacts 250V, 5AAC	2 CO contacts 250V, 5AAC	2 CO contacts 250V, 5AAC
Width	22,5mm	22,5mm	22,5mm	22,5mm
Certificates	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST
Mechanical design				
Terminal capacity	1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end			
Ambient conditions	Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)			
Accessories	PowerModulees TR2 (12 to 440V AC) • DC power supply SNT2 24V DC • sealable intervention protection shield FA-G2			

Temperature monitoring of the motor winding (max. 6 PTC) with fault latch, for temperature probes in accordance with DIN 44081, test function with integrated test/reset key and the following additional functions (G2TFKN02):

- Off Basic function
- +K Short circuit monitoring of thermistor line
- +N Zero-voltage latch
- +K+N Short circuit monitoring and zero-voltage latch



Functions

Sensing & Monitoring Relays Series GAMMA *WatchDog*



Temperature monitoring

- Temperature monitoring of the motor winding in accordance with DIN 44081
- Maximal 6 PTC probes
- Fault latch
- Testfunction with integrated Test/Reset button
- Possibility for external reset
- Supply voltage selectable via PowerModules or by zoom voltage 24 to 240V AC/DC
- 1 CO contact; 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

types	G2TF02 230V AC	G2TF02 110V AC	G2TF01	G2TF01 230V AC
Art.No. (PQ1)	2390104	2390109	2390103	2390102
Art.No. (PQ10)	-	-	-	2390102A
EAN13-Code	900866200241	900866200249	900866200240	900866200238
Measured variable	PTC (motortemperature) max. 6 PTC probes	PTC (motortemperature) max. 6 PTC probes	PTC (motortemperature) max. 6 PTC probes	PTC (motortemperature) max. 6 PTC probes
Measured range	total resistance cold <1,5kΩ terminals T1-T2	total resistance cold <1,5kΩ terminals T1-T2	total resistance cold <1,5kWterminals T1-T2	total resistance cold <1,5kWterminals T1-T2
Measuring voltage	≤2,5V DC at R >4,0kΩ (DINVDE 0660 part 302)	≤2,5V DC at R >4,0kΩ (DINVDE 0660 part 302)	≤2,5V DC at R >4,0kW(DINVDE 0660 Part 302)	≤2,5V DC at R >4,0kW(DINVDE 0660 Part 302)
Controls	Test/Reset button	Test/Reset button	Test/Reset button	Test/Reset button
Indicators (LEDs)	U • Failure	U • Failure	U • Failure	U • Failure
Functions	Overtemperature	Overtemperature	Overtemperature	Overtemperature
Response value	3,6kΩ	3,6kΩ	3,6kΩ	3,6kΩ
Release value	1,8kΩ	1,8kΩ	1,8kΩ	1,8kΩ
Short circuit monitoring	-	-	-	-
Fault latch	yes (auto)	yes (auto)	yes (auto)	yes (auto)
Reset	internal or external terminals R-T2	internal or external terminals R-T2	internal or external terminals R-T2	internal or external terminals R-T2
Supply	230V AC terminals A1-A2	110V AC terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2	230V AC terminals A1-A2
Output	2 CO contacts 250V, 5A AC	2 CO contacts 250V, 5A AC	1 CO contact 250V, 5A AC	1 CO contact 250V, 5A AC
Width	22,5mm	22,5mm	22,5mm	22,5mm
Certificates	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST
Mechanical design				
Terminal capacity				
Ambient conditions				
Accessories				

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm


1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)

PowerModulees TR2 (12 to 440V AC) • DC power supply SNT2 24V DC • sealable intervention protection shield FA-G2


Temperature monitoring of motor winding (max. 6 PTC) with fault latch for probes in accordance with DIN 44081, testfunction with integrated Test/Reset button.

G2TF02



automatic reset by wire link R-T2

Width 22,5mm



Functions



Sensing & Monitoring Relays Series GAMMA

WatchDog



Level monitoring

- Level monitoring of conductive substances
- Pump up or minimum monitoring
- Pump down or maximum monitoring
- Secure galvanic separation of measuring circuit
- 2 CO contacts
- Width 22,5mm
- Industrial design

Connections

types

G2LM20 24V AC

G2LM20 110V AC

G2LM20 230V AC



Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Probe voltage

Probe current

Wiring distance

Control

Indicators (LEDs)

Functions

Trigger level

Tripping delay

Turn-off delay

Supply

Output

Width

Certificates

Mechanical design

Ambient conditions

Accessories

2390201

-

900866200254

level with
conductiv probe

0,25 to 100kΩ

max. 16V AC

max. 7mA

max. 1000m (adjustment <50%)
max. 100m (adjustment <100%)
capacity of cable 100nF/km

Delay on • Delay off • Sensitivity • Function

U + R

Pump up
Pump down

0,25 to 100 kΩ (Sensitivity)

0,5s to 10s

0,5s to 10s

24V AC
terminals A1-A2

2 CO contacts
250V, 5AAC

22,5mm

CE • cULus • GOST

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to 55°C (in accordance with IEC 60068-1); -25 to 40°C (in accordance with UL 508) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) • Vibration resistance: 10 to 55Hz 0,35mm (in accordance with IEC 60068-2-6) • Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)

conductive probes (types SK1, SK2, SK3) • sealable intervention protection shield FA-G2

2390202

-

900866200255

level with
conductiv probe

0,25 to 100kΩ

max. 16V AC

max. 7mA

max. 1000m (adjustment <50%)
max. 100m (adjustment <100%)
capacity of cable 100nF/km

Delay on • Delay off • Sensitivity • Function

U + R

Pump up
Pump down

0,25 to 100 kΩ (Sensitivity)

0,5s to 10s

0,5s to 10s

110V AC
terminals A1-A2

2 CO contacts
250V, 5AAC

22,5mm

CE • cULus • GOST

2390200

-

900866200253

level with
conductiv probe

0,25 to 100kΩ

max. 16V AC

max. 7mA

max. 1000m (adjustment <50%)
max. 100m (adjustment <100%)
capacity of cable 100nF/km

Delay on • Delay off • Sensitivity • Function

U + R

Pump up
Pump down

0,25 to 100 kΩ (Sensitivity)

0,5s to 10s

0,5s to 10s

230V AC
terminals A1-A2

2 CO contacts
250V, 5AAC


22,5mm

CE • cULus • GOST


Level monitoring of conductive substances, timing for tripping delay and turn-off delay separately adjustable and the following functions:

Pump up	Pump up or minimum monitoring
Pump down	Pump down or maximum monitoring

G2LM20



Width 22,5mm



Functions

Sensing & Monitoring Relays Series TREND

Voltage monitoring in 3-phase mains

- Windowfunction (TPW...VN4X)
- Windowfunction with integrated phase sequence monitoring (TPW...VSN4X)
- Connection of neutral wire optional
- Supply voltage selectable via PowerModules or DC power supply
- 1 CO contact
- Width 45mm
- Industrial design

Connections

types

TPW400VSN4X

TPW230VSN4X

TPW115VSN4X

TPW400VN4X



Dimensions

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Controls

Indicators (LEDs)

Functions

Asymmetry

Switching threshold max.

Switching threshold min.

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

2400008

-

900866200298

3(N)~ AC Sinus (48 to 63Hz)

$U_N = 400/230V$ terminals (N)-L1-L2-L3

max • min • Delay (t_1)

max • R • min

WIN+SEQ

crabwise by U_{min}/U_{max}

-20% to 30% from U_N

-30% to 20% from U_N

0,1s to 10s

-

PowerModule TR2 or SNT2 terminals A1-A2

1 CO contact 250V, 5A AC

45mm

CE

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1)


PowerModulees TR2 (12 to 440V AC) • DC power supply SNT2 24V DC




Voltage monitoring in 3-phase mains with adjustable setpoints, adjustable tripping delay and phase sequence monitoring.

WIN	Monitoring the window between Min and Max
WIN+SEQ	Monitoring the window between Min and Max and phase sequence monitoring

TPW...N4X; TPW...SN4X



Width 45mm



Functions



Sensing & Monitoring Relays Series TREND

Voltage monitoring in 3-phase mains

- Phase sequence, phase loss and asymmetry monitoring with fixed asymmetry
- No connection of neutral wire required
- 1 CO contact
- Width 45mm
- Industrial design

Connections

types

TPF230VS4X



2442153

TPF400VS4X



2402058

Dimensions

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Controls

Indicators (LEDs)

Functions

Asymmetry

Switching threshold max.

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

3~ AC Sinus (48 to 63Hz)

$U_N = 230V/132V$
terminals L1-L2-L3

R

Monitoring of phase sequence and phase failure

fixed, approx. 10%

-

-

-

-

-

-

= measuring voltage; 3~ 230V ±15%
terminals L1-L2-L3

1 CO contact
250V, 5A AC

45mm

CE


Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm
 $1 \times 0,5$ to $2,5\text{mm}^2$ with/without multicore cable end • $1 \times 4\text{mm}^2$ without multicore cable end • $2 \times 0,5$ to $1,5\text{mm}^2$ with/without multicore cable end • $2 \times 2,5\text{mm}^2$ flexible without multicore cable end

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1)
-






TPF...S4X



Width 45mm



Functions

Sensing & Monitoring Relays Series TREND

Voltage monitoring in 1-phase mains

- Windowfunction or reverse Windowfunction (TUW4X)
- 1 trigger level with adjustable hysteresis OVER/UNDER (TUH4X)
- Position of output relay selectable
- DIP-Switch for adjusting to AC/DC monitoring and relay position
- Fault latch
- Supply voltage selectable via PowerModules or DC power supply
- 1 CO contact
- Width 45mm
- Industrial design

Connections

types

TUW4X

TUH4X



2420510

2422510

900866200308

900866200309

Voltage AC/DC
AC Sinus (48 to 63Hz)

Voltage AC/DC
AC Sinus (48 to 63Hz)

24V AC/DC; terminals E1-F1(+)
115V AC/DC; terminals E1-F2(+)
230V AC/DC; terminals E1-F3(+)
440V AC/DC; terminals E2-F3(+)

30V AC/DC; terminals E1-F1(+)
60V AC/DC; terminals E1-F2(+)
300V AC/DC; terminals E1-F3(+)
600V AC/DC; terminals E2-F3(+)

max • min • Delay (t_1) • Start (t_2) • AC/DC • REL/REL • Start On/Off

U_s • Hyst • Delay (t_1) • Start (t_2) • AC/DC • REL/REL • Start On/Off

max • R • min

U • R

WIN • reverse WIN

1 trigger level with hysteresis (OVER/UNDER)

-20% to 30% from U_N

trigger level U_s : 10% to 100% from U_N

-30% to 20% from U_N

Hysteresis: 5% to 50% from U_s

$t_1 = 0,1s$ to 10s

$t_1 = 0,1s$ to 10s

$t_2 = 0,1s$ to 10s

$t_2 = 0,1s$ to 10s

selectable

selectable

PowerModule TR2 or SNT2
terminals A1-A2

PowerModule TR2 or SNT2
terminals A1-A2

1 CO contact
250V, 5AAC

1 CO contact
250V, 5AAC

45mm

45mm

CE

CE

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measuring ranges (U_N)

Controls

Indicators (LEDs)

Functions

Switching threshold max.

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1)

PowerModulees TR2 (12 to 440V AC) • DC power supply SNT2 24V DC

**TUW:**




AC/DC voltage monitoring in 1-phase mains with adjustable thresholds, timing for start-up suppression and tripping delay separately adjustable and the following functions (selectable by means of DIP switch)

- DIP-Switch 1: AC/DC preselection
- DIP-Switch 2: Monitoring inside (W) or outside (R) the window between U_{min} and U_{max}
- DIP-Switch 3: ON Relay picks up during the start-up suppression time (t2)
OFF Relay remains in off position during the start-up suppression time (t2)

TUH:

AC/DC overvoltage monitoring in 1-phase mains with adjustable threshold, timing for start-up suppression and tripping delay separately adjustable and adjustable hysteresis and the following functions (selectable by means of DIP-switch)

- DIP-Switch 1: AC/DC preselection
- DIP-Switch 2: REL relay in-on position if error occurs REL relais in off-position if error occurs
- DIP-Switch 3: ON Relay picks up during the start-up suppression time (t2)
OFF Relay remains in off position during the start-up suppression time (t2)

TUW**TUH****Width 45mm****Functions****Sensing & Monitoring Relays Series TREND**

Current monitoring in 1-phase mains

- Windowfunction (TIW4X)
- 2 trigger level (TIF)
- Hysteresis OVER/UNDER (TIH4X)
- Position of output relay selectable (TIW4X; TIH4X)
- DIP-Switch for adjusting to AC/DC monitoring and relay position (TIW4X; TIH4X)
- Fault latch (TIW4X; TIH4X)
- Permissible continuous load on measuring input 15A(TIF)
- Supply voltage selectable via PowerModules or DC power supply (TIW4X; TIH4X)
- 1 CO contact; 2 CO contacts; Width 45mm; Industrial design

Connections**types****TIW4X****TIH4X****TIF30-300mAAC4X**

Art.No. (PQ1)	2430890	2432610	2432894
Art.No. (PQ10)	-	-	-
EAN13-Code	900866200311	900866200312	900866200313
Measured variable	Current AC/DC AC Sinus (48 to 63Hz)	Current AC/DC AC Sinus (48 to 63Hz)	Current AC AC Sinus (48 to 63Hz)
Measuring ranges	100mA AC/DC; terminals K-I3(+) 1A AC/DC; terminals K-I2(+) 10A AC/DC; terminals K-I1(+)	100mA AC/DC; terminals K-I3(+) 1A AC/DC; terminals K-I2(+) 10A AC/DC; terminals K-I1(+)	15A AC; terminals K-I
Controls	max • min • Delay (t ₁) • Start (t ₂) • AC/DC • REL/REL • Start On/Off	I _s • Hyst • Delay (t ₁) • Start (t ₂) • AC/DC • REL/REL • Start On/Off	-
Indicators (LEDs)	max • R • min	U • R	U • R
Functions	WIN	1 trigger level with hysteresis (OVER/UNDER)	UNDER
Switching threshold max.	10% to 100% from I _N	trigger level I _s ; 10% to 100% from I _N	fixed, 30mA fixed, 300mA
Tripping delay	5% to 50% from I _N	Hysteresis: 5% to 50% from I _s	Hysteresis: fixed, approx. 5%
Start-up suppression time	t ₁ = 0,1s to 10s	t ₁ = 0,1s to 10s	-
Fault latch	t ₂ = 0,1s to 10s	t ₂ = 0,1s to 10s	-
Supply	selectable	selectable	-
Output	PowerModule TR2 or SNT2 terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2	230V AC terminals A1-A2
Width	1 CO contact 250V, 5A AC	1 CO contact 250V, 5A AC	2 CO contacts 250V, 5A AC
Certificates	45mm	45mm	45mm
Mechanical design	CE	CE	CE
Terminal capacity	Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm		
Ambient conditions	1 x 0,5 to 2,5mm ² with/without multicore cable end • 1 x 4mm ² without multicore cable end • 2 x 0,5 to 1,5mm ² with/without multicore cable end • 2 x 2,5mm ² flexible without multicore cable end		
Accessories	Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1)		
	PowerModules TR2 (12 to 440V AC) • DC power supply SNT2 24V DC • Current Transformers DWS and WSW		

Dimensions

Art.No. (PQ1)	2430890	2432610	2432894
Art.No. (PQ10)	-	-	-
EAN13-Code	900866200311	900866200312	900866200313
Measured variable	Current AC/DC AC Sinus (48 to 63Hz)	Current AC/DC AC Sinus (48 to 63Hz)	Current AC AC Sinus (48 to 63Hz)
Measuring ranges	100mA AC/DC; terminals K-I3(+) 1A AC/DC; terminals K-I2(+) 10A AC/DC; terminals K-I1(+)	100mA AC/DC; terminals K-I3(+) 1A AC/DC; terminals K-I2(+) 10A AC/DC; terminals K-I1(+)	15A AC; terminals K-I
Controls	max • min • Delay (t ₁) • Start (t ₂) • AC/DC • REL/REL • Start On/Off	I _s • Hyst • Delay (t ₁) • Start (t ₂) • AC/DC • REL/REL • Start On/Off	-
Indicators (LEDs)	max • R • min	U • R	U • R
Functions	WIN	1 trigger level with hysteresis (OVER/UNDER)	UNDER
Switching threshold max.	10% to 100% from I _N	trigger level I _s ; 10% to 100% from I _N	fixed, 30mA fixed, 300mA
Tripping delay	5% to 50% from I _N	Hysteresis: 5% to 50% from I _s	Hysteresis: fixed, approx. 5%
Start-up suppression time	t ₁ = 0,1s to 10s	t ₁ = 0,1s to 10s	-
Fault latch	t ₂ = 0,1s to 10s	t ₂ = 0,1s to 10s	-
Supply	selectable	selectable	-
Output	PowerModule TR2 or SNT2 terminals A1-A2	PowerModule TR2 or SNT2 terminals A1-A2	230V AC terminals A1-A2
Width	1 CO contact 250V, 5A AC	1 CO contact 250V, 5A AC	2 CO contacts 250V, 5A AC
Certificates	45mm	45mm	45mm
Mechanical design	CE	CE	CE
Terminal capacity	Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm		
Ambient conditions	1 x 0,5 to 2,5mm ² with/without multicore cable end • 1 x 4mm ² without multicore cable end • 2 x 0,5 to 1,5mm ² with/without multicore cable end • 2 x 2,5mm ² flexible without multicore cable end		
Accessories	Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1)		
	PowerModules TR2 (12 to 440V AC) • DC power supply SNT2 24V DC • Current Transformers DWS and WSW		


TIW: AC/DC current monitoring in 1-phase mains with adjustable thresholds, timing for start-up suppression and tripping delay separately adjustable and the following functions (selectable by means of DIP-switch)

DIP-Switch 1: AC/DC preselection
 DIP-Switch 2: W Monitoring inside (W) the window between I_{min} and I_{max}
 R Monitoring outside (R) the window between I_{min} and I_{max}
 DIP-Switch 3: ON Relay picks up during the start-up suppression time (t2)
 OFF Relay remains in off position during the start-up suppression time (t2)


TIH: AC/DC overcurrent monitoring in 1-phase mains with adjustable threshold, timing for start-up suppression and tripping delay separately adjustable and adjustable hysteresis and the following functions (selectable by means of DIP-switch)

DIP-Switch 1: AC/DC preselection
 DIP-Switch 2: REL relay in on-position if error occurs. REL relay in off-position if error occurs
 DIP-Switch 3: ON Relay picks up during the start-up suppression time (t2)
 OFF Relay remains in off position during the start-up suppression time (t2)

TIF: Consumer failure detection for AC-current in 1-phase mains with 2 fixed thresholds (selectable via bridge X1-X2)



Width 45mm



Functions

Sensing & Monitoring Relays Series TREND

Temperature monitoring

- Temperature monitoring of motor winding
- Maximum of 6 PTC probes per measuring circuit
- 2 measuring circuits (TDT4X)
- Fault latch for measuring circuit 2 (TDT4X)
- Short circuit monitoring of PTC circuits
- Supply voltage selectable via PowerModules or DC power supply (TDT4X)
- 1 NO contact; 1 CO contact per measuring circuit (TDT4X)
- Width 22,5mm or 45mm
- Industrial design

Connections

types

TDT4X

TT2X 24V AC

TT2X 230V AC



Dimensions

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Measuring voltage

Controls

Indicators (LEDs)

Functions

Response value

Release value

Short circuit monitoring

Fault latch

Reset

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

2480090

-

900866200328

2 x PTC (motortemperature) max. 2 x 6 PTC probes

total resistance cold <1.5k Ω terminals 1T1-T2 (circuit 1) terminals 2T1-T2 (circuit 2)

max. 12V DC

Test/Reset button

U • Failure 1T1-T2 • Failure 2T1-T2

Overtemperature

3,3k Ω

1,8k Ω

<15 Ω

yes (circuit 2)

internal or external terminals 2R1-T2/2R2

PowerModule TR2 or SNT2 terminals A1-A2

1 CO contact each circuit 250V, 5A AC

45mm

CE

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm
 1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1)


PowerModule TR2 (12 to 440V AC) • DC power supply SNT2 24V DC



Sensing & Monitoring Relays Series TREND




TDT4X TT2X



Width 22,5mm

Width 45mm



Functions



Level monitoring

- Level monitoring of conductive substances
- Pump up or minimum monitoring
- Pump down or maximum monitoring
- 1 CO contact
- Width 45mm
- Industrial design

Connections

types

TLH4X 24V AC

TLH4X 230V AC

TLC4X 230V AC



Dimensions

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measuring ranges

Probe voltage

Probe current

Wiring distance

Control

Indicators (LEDs)

Functions

Trigger level

Tripping delay

Turn-off delay

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

2472012

-

900866200317

conductiv probe min.
conductiv probe max.
terminals E1-E2-E3

0,25 to 5kΩ / 5 to 100kΩ

max. 16VAC

max. 7mA / max. 200µA

max. 1000m / max. 100m

Sensitivity • Delay on (t_1) • Delay off (t_2) • Function • Measuring ranges

U + R

Pump up
Pump down

0,25 to 5kΩ / 5 to 100kΩ
(Sensitivity)

0,5s to 10s (t_1)

0,5s to 10s (t_2)

24V AC
terminals A1-A2

1 CO contact
250V, 5A AC

45mm

CE

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required) • IP rating IP20 • Tightening torque max. 1Nm • 1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 3 (in accordance with IEC 60664-1) conductive probes (types SK1, SK2, SK3)

TLH:

Level monitoring of conductive substances, timing for tripping delay and turn-off delay separately adjustable and the following functions:


Pump down Pump down or maximum monitoring
Pump up Pump up or minimum monitoring

TLC:


Level monitoring of conductive substances with adjustable threshold, fixed tripping delay and turn-off delay and the following functions:

Pump down Pump down or maximum monitoring
Pump up Pump up or minimum monitoring


Connection of 3-probes (pump up/down)



Connection of 2-probes (Minimum-/Maximum monitoring)



Width 45mm



Functions



Sensing & Monitoring Relays Series KAPPA

WatchDog



Voltage and current monitoring of mains

- AC voltage monitoring in 1- and 3-phase mains (K3YM)
- AC/DC voltage monitoring in 1-phase mains (K3UM)
- AC current monitoring in 1-phase mains (K3IM)
- Monitoring of phase sequence, phase failure and asymmetry (K3PF)
- Monitoring of phase failure; monitoring of phase sequence selectable (K3YM)
- Multifunction (K3YM; K3IM; K3UM)
- Supply voltage = measuring voltage (K3PF; K3YM; K3UM)
- Supply voltage = 230V (K3IM)
- 2 CO contacts; Width 38mm; Plug-in mounting

Connections

types

K3YM400VSY20	K3PF400VSY02	K3UM230VAC02	K3UM24VDC02	K3IM5AACL20 230V
--------------	--------------	--------------	-------------	------------------



Dimensions

Art.No. (PQ1)	1380402	1380301	1380107	1380106	1380202
Art.No. (PQ10)	-	-	-	-	-
EAN13-Code	9008662005419	9008662005426	9008662005396	9008662005402	9008662005433
Measured variable	3(N)~ AC Sinus (48 to 63Hz)	3(N)~ AC Sinus (48 to 63Hz)	Voltage AC AC Sinus (48 to 63Hz)	Voltage DC	Current AC AC Sinus (48 to 63Hz)
Measured range	$U_n = 400/230V$ pins (S10)-S5-S6-S7	$U_n = 400/230V$ pins (S10)-S5-S6-S7	230V AC pins S5-S7	24V DC pins S5-S7	5A AC pins S5-S7
Control	ASYM • Max • Min • Function / Delay	ASYM	Max • Min • Function	Max • Min • Function	Start • Max • Min • Function • Delay
Indicators (LEDs)	ASYM • SEQ • Max • Min • R	U • R	U • Max • Min • R	U • Max • Min • R	U/t • Max • Min • R
Functions	UNDER • UNDER+SEQ • WIN • WIN+SEQ	Monitoring of phase sequence, phase failure and asymmetry	UNDER • WIN	UNDER • WIN	OVER • OVER+Latch • UNDER • UNDER+Latch • WIN • WIN+Latch
Asymmetry	5% to 30%; Off	5% to 30%; Off	-	-	-
Switching threshold max.	80% to 130% of U_n	-	80% to 120% of U_n	80% to 130% of U_n	10% to 100% of I_n
Switching threshold min.	70% to 120% of U_n	-	70% to 110% of U_n	75% to 125% of U_n	5% to 95% of I_n
Hysteresis	adjustable	-	adjustable	adjustable	adjustable
Tripping delay	0,1s to 10s	fixed circa 100ms	-	-	0,1s to 10s
Start-up suppression time	-	-	-	-	0s to 10s
Fault latch	-	-	-	-	selectable
Supply	= measuring voltage 3(N)~400/230V -30% to +30% pins (S10)-S5-S6-S7	= measuring voltage 3(N)~400/230V -30% to +30% pins S5-S7	= measuring voltage 230V AC -30% to +20% pins S5-S7	= measuring voltage 24V DC -25% to +30% pins S5-S7	230V AC -15% to +10% pins S2-S10
Output	2 CO contacts 250V, 5A AC	2 CO contacts 250V, 5A AC	2 CO contacts 250V, 5A AC	2 CO contacts 250V, 5A AC	2 CO contacts 250V, 5A AC
Width	38mm	38mm	38mm	38mm	38mm
Certificates	CE • GOST	CE • GOST	CE • GOST	CE • GOST	CE • GOST
Mechanical design	Self-extinguishing plastic housing, IP rating IP40 • Mounted on 11-pole screw terminal socket in accordance with IEC 60067-1-18a • Mounting position any				
Ambient conditions	Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 2, if built in 3 (in accordance with IEC 60664-1)				
Accessories	Relay socket R11X, ES12				

K3YM: Voltage monitoring in 1-phase- and 3-phase mains with adjustable thresholds, adjustable tripping delay, monitoring of phase failure and monitoring of phase sequence selectable.

K3IM: AC current monitoring in 1-phase mains with adjustable thresholds, adjustable hysteresis and tripping delay.

K3UM: AC/DC voltage monitoring in 1-phase mains with adjustable thresholds and adjustable hysteresis.

K3PF: Monitoring of phase sequence, phase failure and asymmetry with adjustable asymmetry, connection of neutral wire optional.

OVER Overcurrent monitoring

UNDER Undercurrent or undervoltage monitoring

WIN Monitoring the window between Min and Max

OVER+Latch Overcurrent monitoring with fault latch

UNDER+Latch Undercurrent monitoring with fault latch


WIN+Latch Monitoring the window between Min and Max with fault latch

UNDER+SEQ Undervoltage monitoring and monitoring of phase sequence

WIN+SEQ Monitoring the window between Min and Max and monitoring of phase sequence


K3UM24VDC02

K3UM230VAC02




K3IM5AACL20 230V

K3PF400VSY02



K3YM400VSY20

Width 38mm



Functions



Sensing & Monitoring Relays Series ENYA

Voltage monitoring in 3- and 1-phase mains

WatchDog



UNDERvoltage monitoring

Integrated testswitch (E3YF400VT02 0.85)

Start-up delay time in accordance with VDE 0108-100 and VDE 0100-718 (E3YF400VE20 0.85)

Supply voltage = measuring voltage

2 CO contacts

Width 35mm

Installation design

Connections

types

E3YF400V02 0.85

E3YF400VE20 0.85

E3YF400VT02 0.85

E3YF400VT02 HTV 0.85



Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Control

Indicators (LEDs)

Functions

Asymmetry

Switching threshold max.

Switching threshold min.

Hysteresis

Tripping delay

Start-up delay time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

1341401

-

-

9008662005303

3N~

AC Sinus (48 to 63Hz)

$U_N = 400/230V$

terminals N-L1-L2-L3

-

-

U + R

UNDER

-

UNDER

TEST (R=OFF)

-

-

approx. 5%

fixed, approx. 200ms

-

60 sec

-

-

= measuring voltage

3N~400/230V -30% to +10%

terminals N-L1-L2-L3

2 CO contacts

250V, 5A AC

35mm

CE • cULus • GOST

-

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 2 (in accordance with IEC 60664-1)

-

= measuring voltage

3N~400/230V -30% to +10%

terminals N-L1-L2-L3

2 CO contacts

250V, 5A AC

35mm

CE • cULus • GOST

-

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 2 (in accordance with IEC 60664-1)

-

= measuring voltage

3N~400/230V -30% to +10%

terminals N-L1-L2-L3

2 CO contacts

250V, 5A AC

35mm

CE • cULus • GOST

-

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 2 (in accordance with IEC 60664-1)

-

= measuring voltage

3N~400/230V -30% to +10%

terminals N-L1-L2-L3

2 CO contacts

250V, 5A AC

35mm

CE • cULus • GOST

-

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 2 (in accordance with IEC 60664-1)

-

E3YF400V02 0.85




Undervoltage monitoring in single-phase and 3-phase mains
UNDER Undervoltage monitoring

E3YF400VT02 0.85

Undervoltage monitoring in single-phase and 3-phase mains
UNDER Undervoltage monitoring
T Integrated test switch

E3YF400VE20 0.85

Undervoltage monitoring in single-phase and 3-phase mains
UNDER Undervoltage monitoring
On delay as per VDE 0100-718

E3YF**E3YF**

Width 35mm

Functions**Sensing & Monitoring Relays Series ENYA**

Voltage monitoring in 3- and 1-phase mains

WatchDog

- Undervoltage monitoring
- Integrated testswitch (E1YF400VT01 0.85)
- Supply voltage = measuring voltage
- 1 CO contact
- Width 17,5mm
- Installation design

Connections**Type**

E1YF400V01 0.85

E1YF400VT01 0.85

E1YF400V01 0.70

**Dimensions****Connections**

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Control

Indicators (LEDs)

Functions

Asymmetry

Switching threshold min.

Switching threshold min.

Hysteresis

Tripping delay

Start-up delay time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

1340402

1340402A

900866200057

3N~ AC Sinus (48 to 63Hz)

 $U_N = 400/230V$

terminals N-L1-L2-L3

-

R

UNDER

TEST (R=OFF)

-

-

fixed 195,5V (L-N)

in accordance with

VDE 0100-718

VDE 0108-100

 $0,85 \times U_N$

ca. 5%

fixed, ca. 200ms

-

-

fixed 195,5V (L-N)

in accordance with

VDE 0100-718

VDE 0108-100

 $0,85 \times U_N$

ca. 5%

fixed, ca. 200ms

-

-

fixed 161V (L-N)

-

ca. 5%

-

ca. 5%

-

-

1340406

-

900866200487

3N~ AC Sinus (48 to 63Hz)

 $U_L = 400/230V$

terminals N-L1-L2-L3

-

Testfunction

L1 • L2 • L3 • R

UNDER

TEST (R=OFF)

-

-

fixed 195,5V (L-N)

in accordance with

VDE 0100-718

VDE 0108-100

 $0,85 \times U_N$

ca. 5%

fixed, ca. 200ms

-

-

fixed 161V (L-N)

-

ca. 5%

-

1340410

-

9008662006140

3N~ AC Sinus (48 to 63Hz)

 $U_L = 400/230V$

terminals N-L1-L2-L3

-

R

UNDER

TEST (R=OFF)

-

-

fixed 161V (L-N)

-

ca. 5%

-

3N~ AC Sinus (48 to 63Hz)

 $U_L = 400/230V$

terminals N-L1-L2-L3

-

1 CO contact

250V, 5A AC

17,5mm

CE • cULus • GOST

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 2 (in accordance with IEC 60664-1)

-

-

-

-

-

-

E1YF400V01 0.85

Voltage monitoring in 1-phase and 3-phase mains

UNDER Undervoltage monitoring


E1YF400VT01 0.85

Voltage monitoring in 1-phase and 3-phase mains


UNDER Undervoltage monitoring

T Integrated testswitch

E1YF



Width 17,5mm



Functions

**Sensing & Monitoring Relays Serie ENYA**

Voltage monitoring in 3- and 1-phase mains

WatchDog


- Multifunction
- Monitoring of phase failure
- Monitoring of phase sequence selectable
- Connection of neutral wire optional
- Supply voltage = measuring voltage
- 1 CO contact; 2 CO contacts
- Width 17,5mm; 35mm
- Installation design

Connections

types E3YM230VS20 E1YM400VS10 E1YM480Y/277VS10



Dimensions

Art.No. (PQ1)	1340406	1340405	1340409
Art.No. (PQ10)	-	-	-
EAN13-Code	9008662006393	900866200484	9008662006768
Measured variable	3(N)~ AC Sinus (48 bis 63Hz) $U_N = 230/132V$ terminals (N)-L1-L2-L3	3(N)~ AC Sinus (48 bis 63Hz) $U_N = 400/230V$ terminals (N)-L1-L2-L3	3(N)~ AC Sinus (48 bis 63Hz) $U_N = 480/277V$ terminals L1-L2-L3
Measured range	Delay • Max • Min • Function SEQ • Max • Min • R	Delay • max • min • Function SEQ • max • min • R	Delay • max • min • Function SEQ • max • min • R
Control	UNDER UNDER+SEQ WIN WIN+SEQ	UNDER UNDER+SEQ WIN WIN+SEQ	UNDER UNDER+SEQ WIN WIN+SEQ
Indicators (LEDs)	-	-	-
Functions	80% to 130% of U_N	80% to 130% of U_N	75% to 110% of U_N
Asymmetry	70% to 120% of U_N	70% to 120% of U_N	65% to 100% of U_N
Switching threshold min.	-	-	-
Switching threshold max.	0 to 10s	0,1 to 10s	0,1 to 10s
Hysteresis	-	-	-
Tripping delay	-	-	-
Start-up delay time	-	-	-
Fault latch	-	-	-
Supply	= measuring voltage 3(N)-230/132V -30% to +30% terminals (N)-L1-L2-L3	= measuring voltage 3(N)-400/230V -30% to +30% terminals (N)-L1-L2-L3	= measuring voltage 3-480/277V -35% to +10% terminals L1-L2-L3
Output	2 CO contacts 250V, 5A AC	1 CO contact 250V, 5A AC	1 CO contact 250V, 5A AC
Width	35mm	17,5mm	17,5mm
Certificates	CE • cULus • GOST	CE • cULus • GOST	CE • GOST
Mechanical design	Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm		
Terminal capacity	1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end		
Ambient conditions	Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 2 (in accordance with IEC 60664-1)		
Accessories	-		


E1YM, E3YM

Voltage monitoring in single-phase and 3-phase mains with adjustable thresholds, adjustable trip delay, monitoring of phase breakdown and phase sequence and the following functions that can be selected via rotary switches:


UNDER
UNDER+SEQ
WIN
WIN+SEQ

Undervoltage monitoring
Undervoltage and phase sequence monitoring
Window monitoring, monitoring of range between the min and max thresholds
Monitoring the window between Min and Max and monitoring of phase sequence


E3YM230VS20




E1YM400VS10



Width 17,5mm



Width 35mm



Functions



Sensing & Monitoring Relays Series ENYA

Voltage monitoring in 3- and 1-phase mains

WatchDog



- Undervoltage monitoring
- Supply voltage = measuring voltage
- 1 CO contact; 2 CO contacts
- Width 17,5mm; 35mm
- Installation design

Connections

types

E3YU400V02




E1YU400V01

Art.No. (PQ1)	1341403	1340403
Art.No. (PQ10)	-	-
EAN13-Code	9008662005617	900866200059
Measured variable	3(N)~ AC Sinus (48 to 63Hz)	3(N)~ AC Sinus (48 to 63Hz)
Measured range	$U_s = 400/230V$ terminals N-L1-L2-L3	$U_s = 400/230V$ terminals N-L1-L2-L3
Control	U_s	U_s
Indicators (LEDs)	L1 • L2 • L3 • R	L1 • L2 • L3 • R
Functions	UNDER	UNDER
Asymmetry	-	-
Switching threshold min.	160-240V (L-N)	160-240V (L-N)
Hysteresis	approx. 5%	approx. 5%
Tripping delay	fixed approx. 200ms	fixed, approx. 200ms
Start-up suppression time	-	-
Fault latch	-	-
Supply	= measuring voltage 3(N)-400/230V -30% to +10% terminals (N)-L1-L2-L3	= measuring voltage 3(N)-400/230V -30% to +10% terminals (N)-L1-L2-L3
Output	2 CO contacts 250V, 5A AC	1 CO contact 250V, 5AAC
Width	35mm	17,5mm
Certificates	CE • cULus • GOST	CE • cULus • GOST
Mechanical design	Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm	
Terminal capacity	1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end	
Ambient conditions	Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3 class 3K3) • Pollution degree: 2 (in accordance with IEC 60664-1)	
Accessories	-	

Dimensions



E1YU, E3YU

Undervoltage monitoring in 4-wire systems (each phase against neutral), with adjustable setpoint (E1YU) and with fixed hysteresis.

E3YU**E1YU**

Width 17,5mm

Width 35mm

**Functions****Sensing & Monitoring Relays Series ENYA**

Voltage monitoring in 3- and 1-phase mains

- Voltage monitoring in accordance with VDE 0126-1-1
- Quick net error recognition
- Supply voltage = measuring voltage
- 2 CO contacts
- Width 35mm
- Installation design

WatchDog

**Connections****types****Connections****Art.No. (PQ1)****Art.No. (PQ10)****EAN13-Code****Measured variable****Measured range****Control****Indicators (LEDs)****Functions****Asymmetry****Switching threshold min.****Delay****On-delay****Fault latch****Supply****Output****Width****Certificates****Mechanical design****Terminal capacity****Ambient conditions****Accessories**

E3YF400VFAL02



1341400

-

9008662005198

3(N)~

AC Sinus (48 to 63Hz)

 $U_i = 400/230V$
terminals (N)-L1-L2-L3

Latch • Average

U/t • R

WIN

WIN+LATCH

-

fixed +15% from U_N
fixed -20% from U_N 10-minute-average: +10% to +15% from U_N $U \leq 80\%$ from U_N <200ms
 $U \geq 115\%$ from U_N <200ms
phase failure <20ms

fixed 30s

selectable

= measuring voltage
3(N)-400/230V
terminals (N)-L1-L2-L32 CO contacts
250V, 5A AC

35mm

CE • cULus • GOST

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end



Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 2, if built in 3 (in accordance with IEC 60664-1)

-


E3YF400VFA02

Voltage monitoring in 3-phase mains in accordance with VDE 0126-1-1 with fixed tripping delay, fixed threshold, adjustable 10-minute-average and selectable fault latch by means of rotary switch.

WIN	Monitoring the fixed adjusted range
WIN+Latch	Monitoring the fixed adjusted range with fault latch

E3YF400VFA02

Width 35mm



Functions

**Sensing & Monitoring Relays Series ENYA**

Voltage monitoring in 3- and 1-phase mains

WatchDog

- Monitoring of phase sequence, phase failure and asymmetry
- Connection of neutral wire optional (E1PF400VSY01, E3PF400VSY02)
- Supply voltage = measuring voltage
- 1 CO contact; 2 CO contacts
- Width 17,5mm or 35mm
- Installation design

Connections

types

E3PF400VSY02

E1PF400VSY01

E1PF480Y/277VSY10



Dimensions

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Control

Indicators (LEDs)

Functions

Asymmetry

Switching threshold max.

Switching threshold min.

Hysteresis

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

1341300

1340300

1340305

-

-

-

900866200513

900866200486

-

3(N)~ AC Sinus (48 to 63Hz)

3(N)~ AC Sinus (48 to 63Hz)

3~ AC Sinus (48 to 63Hz)

 $U_N = 400/230V$ terminals (N)-L1-L2-L3 $U_N = 400/230V$ terminals (N)-L1-L2-L3

208V to 480V terminals L1-L2-L3

ASYM

ASYM

Delay • ASYM

U • R

U • R

U • Failure • R

Monitoring of phase sequence, phase failure and asymmetry

Monitoring of phase sequence, phase failure and asymmetry

Monitoring of phase sequence, phase failure and asymmetry

5% to 25%, OFF

5% to 25%; OFF

5% to 25%, OFF

-

-

-

-

-

-

-

-

-

fixed, approx. 100ms

fixed, approx. 100ms

0,1s to 20s

-

-

-

-

-

-

= measuring voltage 3(N)-400/230V -30% to +30% terminals (N)-L1-L2-L3

= measuring voltage 3(N)-400/230V -30% to +30% terminals (N)-L1-L2-L3

= measuring voltage 3~208/120V to 480/277V

-10% to +10% from U_N terminals L1-L2-L3

-

-

-

2 CO contacts 250V, 5A AC

1 CO contact 250V, 5A AC

1 CO contact 250V, 5A AC

35mm

17,5mm

17,5mm

CE • cULus • GOST


CE • cULus • GOST

CE • cULus • GOST


Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm
1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 2, if built in 3 (in accordance with IEC 60664-1)
-


E1PF400VSY01




E3PF400VSY02




E1PF480Y/277VSY10



Width 17,5mm



Width 35mm



Functions

Sensing & Monitoring Relays Series ENYA
Voltage monitoring in 1-phase mains

WatchDog



- AC/DC voltage monitoring in 1-phase mains
- Multifunction (E1UM)
- Undervoltage monitoring (E1UU)
- Supply voltage = measuring voltage
- 1 CO contact
- Width 17,5mm
- Installation design

Connections

types

E1UM230V01



E1UU230V01



Dimensions

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measuring ranges

Controls

Indicators (LEDs)

Functions

Switching threshold max.

Switching threshold min.

Hysteresis

Tripping delay

Start-up suppression time

Fault latch

Supply

Output

Width

Certificates

Mechanical design

Terminal capacity

Ambient conditions

Accessories

1340101

-

900866200510

Voltage AC/DC
AC Sinus (48 to 63Hz)24V DC; terminals E-F1(+)
24V AC; terminals E-F2
230V AC; terminals E-F3

Max • Min • Function

U • Max • Min • R

UNDER
WIN80% to 120% from U_N 75% to 115% from U_N

adjustable

-

-

-

 $=$ measuring voltage
24V DC; terminals E-F1(+)
24V AC; terminals E-F2
230V AC; terminals E-F3
-25% to +20%1 CO contact
250V, 5A AC

17,5mm

CE • cULus • GOST

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 2 (in accordance with IEC 60664-1)

-

E1UM

AC/DC voltage monitoring in 1-phase mains with adjustable thresholds and hysteresis.

UNDER

Undervoltage monitoring


WIN Monitoring the window between Min and Max

E1UU


AC/DC UNDERVoltage monitoring in 1-phase mains with adjustable threshold and fixed hysteresis.

UNDER

Undervoltage monitoring

E1UM; E1UU

Width 17,5mm

**Functions****Sensing & Monitoring Relays Series ENYA**

Current monitoring


WatchDog



- AC/DC current monitoring (E3IM)
- AC current monitoring (E1IM; E1IU)
- Multifunction (E1IM; E3IM)
- Undercurrent monitoring (E1IU)
- Supply voltage 230V (E3IM - galvanically separated)
- 1 CO contact; 2 CO contacts
- Width 17,5mm; 35mm
- Installation design

Connections

types E3IM10AL20 E1IM10AACL10 E1IU5AAC01 E1IU500mAAC01

**Dimensions**


Art.No. (PQ1)	1341200	1340200	1340201	1340204
Art.No. (PQ10)	-	-	-	-
EAN13-Code	900866200594	900866200486	900866200504	9008662005341
Measured variable	Current AC/DC Sinus (16 to 400Hz)	Current AC Sinus (48 to 63Hz)	Current AC Sinus (48 to 63Hz)	Current AC Sinus (48 to 63Hz)
Measuring ranges	100mA AC/DC; terminals k-11 1A AC/DC; terminals k-12 10A AC/DC; terminals k-13	10A AC; terminals Li-Lk	5A AC; terminals Li-Lk	500mA AC; terminals Li-Lk
Controls	Start • Max • Min • Function • Delay	Delay • Max • Min • Function	I_s	I_s
Indicators (LEDs)	U/t • Max • Min • R	U/t • Max • Min • R	U • R	U • R
Functions	OVER OVER+LATCH UNDER UNDER+LATCH WIN WIN+LATCH	OVER OVER+LATCH UNDER UNDER+LATCH WIN WIN+LATCH	UNDER	UNDER
Switching threshold max.	10% to 100% of I_N	10% to 100% of I_N	-	-
Switching threshold min.	5% to 95% of I_N	5% to 95% of I_N	10% to 100% of I_N	10% to 100% of I_N
Hysteresis	adjustable	adjustable	fixed, 10%	fixed, 10%
Tripping delay	0,1s to 10s	0,1s to 10s	-	-
Start-up suppression time	0s to 10s	-	-	-
Fault latch	selectable	selectable	-	-
Supply	230V AC terminals A1-A2 -15% to +15%	230V AC terminals Li-N -15% to +15%	230V AC terminals Li-N -15% to +15%	230V AC terminals Li-N -15% to +15%
Output	2 CO contacts 250V, 5A AC	1 CO contact 250V, 5A AC	1 CO contact 250V, 5A AC	1 CO contact 250V, 5A AC
Width	35mm	17,5mm	17,5mm	17,5mm
Certificates	CE	CE • cULus • GOST	CE • cULus • GOST	CE • cULus • GOST
Mechanical design	Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm			
Terminal capacity	1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end • 2 x 2,5mm² flexible without multicore cable end			
Ambient conditions	Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 2 (in accordance with IEC 60664-1)			
Accessories	Mounting plate MP; Current transformer Series DSW and WSW			

E1IM: DC current monitoring with adjustable thresholds, hysteresis and tripping delay.
E3IM: AC/DC current monitoring with adjustable thresholds, hysteresis and tripping delay.


OVER	Overcurrent monitoring
UNDER	Undercurrent monitoring
WIN	Monitoring the window between Min and Max
OVER+Latch	Overcurrent monitoring with fault latch
UNDER+Latch	Undercurrent monitoring with fault latch
WIN+Latch	Monitoring the window between Min and Max with fault latch

E1IU
AC current monitoring with adjustable threshold and fixed hysteresis.




E1IM




E1IU




E3IM measuring range 100mA; 1A; 10A



Width 17,5mm



Width 35mm



Functions



Sensing & Monitoring Relays Series ENYA

Temperature monitoring

WatchDog



- Temperature monitoring of the motor winding for temperature sensors in accordance with DIN 44081
- Maximum 6 PTC sensors
- Short circuit monitoring of the thermistor line (selectable by means of terminals)
- Optional evaluation of one thermal contact
- Test function with integrated reset key
- Rated isolated voltage on the sensor circuit up to 690V
- 1 CO contact
- Width 35mm
- Installation design

Connections

types

E3TF01



Art.No. (PQ1)

1341600

Art.No. (PQ10)

-

EAN13-Code

900866200512

Measured variable

PTC (motortemperature)
max. 6 PTC probes

Measured range

total resistance cold <1,5kΩ
terminals T1-T2 or T1-T3

Measuring voltage

≤7,5V DC by R ≤4,0kΩ
(in accordance with EN 60947-8)

Controls

Test/Reset button

Indicators (LEDs)

U • Failure

Functions

Overtemperature

Response value

≥3,6kΩ

Release value

≤1,65kΩ

Short circuit monitoring

<20Ω

Fault latch

yes

Reset

internal or external
terminals R1-R2

Supply

230V AC
terminals A1-A2

Output

1 CO contacts
250V, 5AAC

Width

35mm

Certificates

CE • cULus • GOST

Mechanical design

Self-extinguishing plastic housing, IP rating IP40 • Mounted on DIN-Rail TS 35 in accordance with EN 60715 • Mounting position any • Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20 • Tightening torque max. 1Nm

Terminal capacity

1 x 0,5 to 2,5mm² with/without multicore cable end • 1 x 4mm² without multicore cable end • 2 x 0,5 to 1,5mm² with/without multicore cable end
• 2 x 2,5mm² flexible without multicore cable end

Ambient conditions

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1) • Storage temperature: -25 to +70°C • Transport temperature: -25 to +70°C • relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3) • Pollution degree: 2 (in accordance with IEC 60664-1)

Accessories

-

Dimensions


Ambient conditions

-


Temperature monitoring of the motor winding (max. 6 PTC) with fault latch for temperature sensors in accordance with DIN 44081, short circuit monitoring of the thermistor line (selectable by means of terminals), integrated test/reset key.

Note:
Only one of this circuit versions (either monitoring of the temperature sensor or monitoring of the thermal contact) can be executed.


Monitoring Temperature sensor



Monitoring Thermal contact



Width 35mm



Functions



Sensing & Monitoring Relays Series ENYA

Level monitoring

- Level monitoring of conductive liquids
- Multifunction
- Reinforced insulation of the measuring circuit
- 1 CO contact
- Width 35mm
- Installation design



Connections

types

E3LM10



1341500

900866200509

level with
conductiv probe

0,25 to 100kΩ

12V AC

max. 7mA

max. 1000m (adjustment <50%)
max. 100m (adjustment <100%)
capacity of cable 100nF/km

Delay ON • Delay OFF • Sensitivity • Function

U • R

Pump up
Pump down

0,25 to 100 kΩ (Sensitivity)

0,5s to 10s

0,5s to 10s

230V AC
terminals A1-A21 CO contact
250V, 5A AC

35mm

CE • cULus • GOST

Art.No. (PQ1)

Art.No. (PQ10)

EAN13-Code

Measured variable

Measured range

Probe voltage

Probe current

Wiring distance

Control

Indicators (LEDs)

Functions

trigger level

Tripping delay

Turn-off delay

Supply

Output

Width

Certificates

Mechanical
design

Terminal capacity

Ambient
conditions

Accessories

Conductive probes (types SK1, SK2, SK3)

Dimensions


E3LM10

Level monitoring of conductive liquid, timing for tripping delay and turn-off delay separately adjustable and the following functions (selectable by means of rotary switch):

- | | |
|-----------|---------------------------------|
| Pump up | pump up or minimum monitoring |
| Pump down | pump down or maximum monitoring |


Functions

E3LM



Connections

With 35mm



Dimensions